



SPECIFICATIONS:

DESCRIPTION

Wall-mounted sconces featuring handcrafted glasses. 9" sq. model (#8884) and 5" wide model (#8886) are **ADA-compliant**.

LAMPING

Standard: 60W or 75W A19 120V incandescent, suitable for dimming.

CFL: 18W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

LED: 7W LED Replaceable source 120V, non-dimmable, included.

DIFFUSER

Diffuser shall be handcrafted Opal Matte glass.

CONSTRUCTION

Stamped aluminum fitter is powder coated white. Glass is secured by stainless steel set screws.


MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Centered on fixture, except 8886— fixture centerline is positioned 0.75" below box centerline.

LABELS


UL or ETL Listed. Suitable for Wet Locations (interior or exterior use).

Geo 5: #8886




FIXTURE	-	LAMP OPTIONS
888607 8.5" H Opal Matte		(blank) 1x 60W A19 Incan D1 1x 13W Quad 120V LED 1x 7W LED 120V, non-dimmable

Geo 9: #8884



FIXTURE	-	LAMP OPTIONS
888407 9" H Opal Matte		(blank) 1x 60W A19 Incan D1 1x 13W Quad 120V F1 1x 18W TBX 120V LED 1x 7W LED 120V, non-dimmable

Geo 11: #8883



FIXTURE	-	LAMP OPTIONS
888307 11.0" H Opal Matte		(blank) 2x 60W A19 Incan E2 2x 18W Quad 120V K1 1x 32W TBX 120V LED 2x 7W LED 120V, non-dimmable

Ex. 888307
2 Lt. Geo 11 Sconce w/ Opal Matte Glass,
White Finish

Project Information:



GEO SHOWN IN OPAL MATTE

888607
OPAL MATTE



LED SCONCES:

- Total power of only 7 watts
- Non-dimmable
- Rated life: 30,000 hours
- 500 lumens
- CCT: 3000° Kelvin
- CRI: 80+

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.