

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Rhea LED Outdoor Sconce REAW Series

Features

This outdoor LED light is ideal for security and general lighting.
Vertical or horizontal mounting. Fixture mounts to standard junction box (not included).



Emergency Back-Up (Optional '-BB')

- 90 minute run-time
- 9.6VDC LiFePO4 battery
- 8 watts

Construction

Durable metal construction with powder coat finish. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black finish.

Diffuser

White acrylic diffusers.

Electrical

Input 120-277 VAC 60 HZ.
0-10V dimming (120-277V), TRIAC (120V).
Minimum starting temp -4° F / -20°C

Lamping

Fixture includes a LED modules capable of producing:
20W = 900 delivered lumens
25W = 1200 delivered lumens
30W = 1500 delivered lumens
40W = 2000 delivered lumens
Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for wet locations.
Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Black	LED	Delivered Lumens	Adjustable CCT	H	W	D
	20W	900	2700K/2700K/3000K/3500K/4000K	18"	5"	2-1/8"
	20W	900	2700K/2700K/3000K/3500K/4000K	18"	5"	2-1/8"
	25W	1200	2700K/2700K/3000K/3500K/4000K	24"	5"	2-1/8"
	25W	1200	2700K/2700K/3000K/3500K/4000K	24"	5"	2-1/8"
	30W	1500	2700K/2700K/3000K/3500K/4000K	36"	5"	2-1/8"
	30W	1500	2700K/2700K/3000K/3500K/4000K	36"	5"	2-1/8"
	40W	2000	2700K/2700K/3000K/3500K/4000K	48"	5"	2-1/8"
	40W	2000	2700K/2700K/3000K/3500K/4000K	48"	5"	2-1/8"

