



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S13512 - 30 Watt Commercial LED Downlight; 8 in.; Remote Driver; Watt and Color Selectable; 120-347 Volt

- Wattage Selectable
- CCT Selectable
- IC Rated
- Air Tight
- Flicker Free



ELECTRICAL

Technology:	LED
Watts:	30W/22W/16W
Volts:	120V-347V
Lumens:	2500L/2000L/1500L
CRI:	90+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Dimmable Down To %:	100 to 10 percent
Incandescent Equivalent :	125W
Operating Temperature :	-25C (-13F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Hardwire
THD:	<30%
Power Factor :	>0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923135125
Each Quantity:	1
Each Dimensions:	9.53 x 5.04 x 9.29

INFO

Specification Note:	Default Wattage: 30W; FT6 cable between driver and lighting head; Default CCT: 3000K
---------------------	--

PHYSICAL

Finish:	Matte White
Lens Finish:	Frosted
Lens Material:	Polycarbonate (PC)
Dimensions:	H:3.40" DIA:8.66"
Weight (Lbs.):	1.1
Material:	Aluminum

INSTALLATION

Sloped Ceiling Compatible:	No
----------------------------	----


COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	4515181
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
Vapor Tight Fixture Rated:	No
ADA Compliant:	No
Closet Rated:	No
FCC Compliant:	Yes
IP Rating:	IP54
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

**80-867**Universal New Construction Recessed Downlight Mounting Plate; Flat; 3.5-Inch; 4-Inch; 6-Inch; 8-Inch

**80-945**New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 8-inch Recessed Downlights; Up to 8.125-inch hole diameter

**80-953**New Construction Mounting Plate for Stud/Joist mounting of 8-inch Recessed Downlights; Up to 8.063-inch hole diameter

**80-985**6 FOOT REMOTE DRIVER 3-PIN EXT

**S13530**Accessory for CDL Remote Driver - 8in rd matte clear/white trim

**S13531**Accessory for CDL Remote Driver - 8in rd matte clear trim

**S13532**Accessory for CDL Remote Driver - 8in rd matte black trim

**S13542**8" Flat Goof Ring for Commercial Downlights, Round, White Finish, 12.50 OD, 7.38 ID, 0.032 Thick.
