



Installation steps:

- 1-2. Attach the light arm to the central hub base using a lock nut and lock washer.
3. Connect wires of the same color as follows:
 - Connect white wires from light arms to the white wires from the fixture with a wire nut.
 - Connect black wires from light arms to the black wires from the fixture with a wire nut.
- 4-5. Attach the bottom cover on the center hub base with a ball nut.
- 6-8. Determine the wanted height or look of the fixture with the provided stems, and assemble them by screwing them together.
9. Attach the mounting bracket to the outlet box using the mounting screws.
10. Pull out the source wires from the outlet box. Make wire connections using wire nuts as follows:
 - Connect the white wire from the fixture to the white wire from the power source.
 - Connect the black wire from the fixture to the black wire from the power source.
 - Attach the fixture grounding wire to the mounting bracket with the green grounding screw and then connect it to the house grounding wire with a wire nut.
 Carefully tuck the wires back into the outlet box.
- 11-12. Attach the canopy to the outlet and tighten it with two ball nuts.
13. Install the bulbs. (Bulb not included)
14. Screw the shade to the lamp holder.

Notice:

1. Before installation, please check whether the parts are complete and whether the lamps are in good condition.
2. Cut off the power supply before installation, and then perform wiring.
3. Install the lamp body first, and then install the power supply.
4. Installation and maintenance must be carried out by professional and technical personnel.