

## How to Install

1. Measure and drill holes in the wall.
2. Tighten the water heater with screws. The water heater must be installed vertically.
3. Connect the cold water inlet pipe(excluded) to the inlet and the water outlet pipe(excluded) to the outlet.
4. Before connecting the power, fill it with water and check for leaks.
5. Open the hot water faucet until constant water flows from them. Otherwise, damage to the element may occur.

## Specifications

Color: White

Style: Modern

Shape: Rectangle

Material: Brass, ABS, 304 Stainless Steel, 316L Stainless Steel

Surface Treatment: Pickling

Plug: US-Standard

Power Source: Corded Electric

Water Inlet Mode: Bottom Water Inlet

Mounting Type: Wall-Mounted, Floor-Mounted, Under Sink

Temperature Regulation Range: 20-50 °C/68-122 °F

Assembly Required: Yes

Power: 3000W

Voltage: AC 110V

Frequency: 50-60Hz

Waterproof Level: IPX4

Trip Switch: >32A

Screen Type: LED

Water Pressure: 0.04-1.2MPa

Wire Request: Wire Cross Section  $\geq 2.5\text{mm}^2/0.0038\text{in}^2$

Suggest Minimum Reserved Installation Space: 30\*30\*25cm/11.81\*11.81\*9.84in

Gross Weight: 1.1kg/2.42lbs

Net Weight: 0.95kg/2.1lbs

Product Size: 11.6\*7\*19.5cm/4.57\*2.8\*7.68in

Power Cord Length: 1.05m/3.44ft

Tank Length: 16cm/6.3in

Package Size: 23.5\*9.5\*18.5cm/9.25\*3.74\*7.28in