




97011 Product Installation Instructions







Ax1




Bx1




Cx1




Dx1




Ex2




Fx1




Gx1




Hx1




Ix1




Jx1




Kx1




Lx1




Mx1




Nx1










Ox2




Px2







Accessories list

①		Two in one screw (6x28mm)	32pcs +4pcs
②		Two in one nut (10x12mm)	32pcs +4pcs
③		Wood chipping (6x30mm)	12pcs +4pcs
④		Non-slip pads	6pcs +2pcs
⑤		Rebound device & Screw (3x16mm)	8pcs +2pcs
		Iron sheet	4pcs
⑥		Double end connecting line	2pcs
⑦		Wire clamp	2pcs +2pcs
⑧		Fixing clip & screw (3x16mm)	8pcs +4pcs
⑨		Foot nail	4pcs +2pcs
⑩		Hinge	8pcs
		AC/DC Adapter (12V=3.0A)	1pcs
⑪	Anti Fall Hardware  (3.5x14mm) x2 (4x45mm) x2 x2 x4 Double-head screwdriver, use as required  1pcs 2		

Product structure decomposition




①		32pcs	④		6pcs	⑦		2pcs
②		32pcs	⑤	 2pcs	 8pcs	⑧		8pcs
③		12pcs	⑥	 2pcs	⑨		4pcs	




Use parts ① and ②



Step1




Step2



Step3





Use a screwdriver to lock in the direction of the "+" sign




Disassemble along the direction of "-" sign

Step 1



Step 2



②




x2


x2

2

Step 3



①



x4


x4

1

6


Step 4

②





Step 5



②



Step 6




Step 7





Step 8

4




x6


Tear off release paper and stick the black foot pad on the board



Step 9





Gx1




Hx1


Insert the backplane into the slot



Step 10




Step 11





Step 12



②




Step 13





Step 14




Step 15



Step 16



Step 17




Step 18


②




x4



Step 19





Lx1




Mx1


Insert the backplane into the slot



Step 20



Step 21




Step 22



②




x4



Step 23




Step 24





Step 25

⑦  x2



Step 26

8  x8




Step 27

9




x4

Use a hammer to drive the nail into the gap of the wooden board and fix the back board




5




4pcs

10



8pcs



1pcs

11


x2



x2




x2




x2



x4




Step 28





Pay attention to the direction of the door hinge,
rotate the screws to compress the black gasket,
and do not place it in the opposite direction

Step 29



Step 30




Step 31

10





x2




first

When installing a glass door, it is recommended to have two people install it to avoid the glass door colliding or hitting oneself.


Pay attention to the direction of the door hinge during installation




second
Locking screw



Step 32




Step 33




Step 34


The rebound device automatically opens and closes by pressing



Open the glass door



Close the glass door




Step 35



10








x2



Step 36



Install as required




User's Guide

Thank you for purchasing this product. To use this product, please plug it into a 12V DC power supply. Please use if the product works normally after connecting to power.

Introduction

The box is an intelligent controller with 2 touch buttons. It can turn ON/OFF the light, change light colors, and adjust the light luminance.

Product Show



ATTENTION PLEASE

1. If there is no touch response suddenly, Re-plug the power to reset the touch static electricity.
2. If bubbles appear on the panel, remove the protective film.

Operation



This touch button is used to turn on/off, change colors, and adjust brightness.

A. Short touch -> lighting on -> short touch -> change light color -> short touch -> change light color -> short touch -> lighting off. B. Long touch -> adjust the luminance



This touch button is used to turn on/off the induction function.

- A. Short touch to turn on the induction function. It can auto-turn on the light when people are close to the controller in 1 meters. It can auto power off the light when the body is far away from the controller after 30 seconds.
- B. Long touch to turn off the induction function.
- C. Note: When you touch the light button to change the light modes, the induction function will automatically turn off. It is best to turn on this function after selecting the light color and adjusting the brightness you want.