

Model PL S_UL

Collection featuring sinuous, modern shapes, composed of two glass diffusers harmoniously joined by a metal ring. The first diffuser, made of colored transparent glass, visually blends with the second in glossy white glass, which conceals the integrated LED source. The collection has been expanded and is now available in suspension, ceiling, wall, and table versions in various configurations.

GLASS FINISH



ADBC
dark amber white



CRBC
crystal white



TBBC
burnt earth white



VABC
old green white


FRAME FINISH



NEO
matt black 2



OTV
painted brass



FARO PL S ADBC NEO L22 UL

LIGHT SOURCES

1x8,5W 120V/60Hz LED 2700K 8,5W 1200lm DIM2 Phase Cut
1x8,5W 120V/60Hz LED 2700K 8,5W 1200lm DIM3 0-10V Push
1x8,5W 120V/60Hz LED 3000K 8,5W 1200lm DIM2 Phase Cut
1x8,5W 120V/60Hz LED 3000K 8,5W 1200lm DIM3 0-10V Push

TECH DATA

⏚ IP20

VOLUME: Mc 0,11

PACKAGE: N.2

NET WEIGHT: Kg 3,40


GROSS WEIGHT: Kg 5,60

CERTIFICATIONS

International Cert



OTHER VERSIONS AVAILABLE



FARO PL G