

| | | | | | | |
|---|---|--|---|-----------------|-----------------|-----------------|
| <p>① canopy 1PCS</p> <p>② cap nut 2PCS</p> | <p>③ chain 1PCS</p> | <p>④ metal box 1PCS</p> <p>⑤ hanging ring 1PCS</p> <p>⑥ metal cover 1PCS</p> | <p>⑦ bended profile 4PCS</p> <p>⑧ screw</p> <p>⑨ lock nut and teeth lock washer</p> | | | |
| <p>⑩ bended profile 4PCS</p> <p>⑧ screw</p> <p>⑨ lock nut and teeth lock washer</p> | <p>⑪ metal round plate 1PCS</p> <p>⑫ metal round plate 1PCS</p> <p>⑬ end cap 1PCS</p> | <p>⑬ lampshade 1PCS</p> | <p>⑭ light fixture 1PCS</p> | | | |
| <p>⑮ hanging tube 1PCS</p> | <p>⊗ X 1PCS</p> | <p>⊙ X 3PCS</p> | <p>⊙ X 3PCS</p> | <p>⊙ X 3PCS</p> | <p>⊙ X 3PCS</p> | <p>⊙ X 3PCS</p> |

1. Rotate the ring ⑤ to remove out the ring ⑤ and cover ⑥ from metal box ④.
2. Install the profile ⑦ to the box ④ with lock nut and teeth lock washer ⑨, close the cover ⑤ to the box ④ with ring ⑤.

3. Rotate the end cap ⑪ to remove out the end cap ⑪ and cover ⑥ from metal plate ⑫.
4. Install the profile ⑩ to the plate ⑫ with lock nut and teeth lock washer ⑨, close the cover ⑥ to the plate ⑫ with end cap ⑪.

5. Let the wire of the fixture ⑭ go through the hanging tube ⑮, rotate to fix the tube to the fixture.
6. Install the metal frame ⑦ to the lampshade ⑬ with screw ⑧, let the wire of the fixture go through the box ④, rotate to fasten two parts together.
7. Install the metal frame ⑩ to the lampshade ⑬ with screw ⑧.
8. Hang the fixture to the canopy ① with chain ③, let the wire go through the chain ③ and canopy ①.

9. Install the bracket to the ceiling junction box with screw ⑯.
10. Connect the wire to the home line with cap connector ⑰.
11. Install the fixture to the bracket with cap nut ②.
12. Install the bulb ⑱.

Please read carefully before installation!!!
 Note : Please make sure that the electricity is powered off during installation !
 Only a professional electrician should install this kind of product !