

# 4 Light Bath Light

(Tannery Bronze)

Project Name: \_\_\_\_\_

Location: \_\_\_\_\_

Type: \_\_\_\_\_

Qty: \_\_\_\_\_

Comments: \_\_\_\_\_



## Ordering Information

|        |                |
|--------|----------------|
| Finish | Tannery Bronze |
|--------|----------------|

## Dimensions

|                                    |              |
|------------------------------------|--------------|
| Extension                          | 8.00"        |
| Height from center of Wall opening | 3.50"        |
| Base Backplate                     | 30.00 X 4.75 |
| Weight                             | 6.85 LBS     |

## Specifications

|                      |              |
|----------------------|--------------|
| Material             | Steel        |
| Diffuser Description | Satin Etched |

## Electrical

|         |       |
|---------|-------|
| Voltage | 120 V |
|---------|-------|

## Qualifications

|              |      |
|--------------|------|
| Safety Rated | Damp |
|--------------|------|

## Installation

|                          |     |
|--------------------------|-----|
| Install Glass Up or Down | Yes |
|--------------------------|-----|

## Primary Lamping

|                        |              |
|------------------------|--------------|
| Light Source           | Incandescent |
| Lamp Included          | Not Included |
| # of Bulbs/LED Modules | 4            |
| Max or Nominal Watt    | 100W         |
| Socket Wire            | 150          |
| Socket Type            | Medium       |
| Lamp Type              | A19          |

## Dimensions

|        |        |
|--------|--------|
| Height | 8.00"  |
| Width  | 30.00" |

## Alternate Lamps

| Lamp Included | Bulb Listing | Light Source | Max Wattage/Range | Bulb Product ID | Dimming |
|---------------|--------------|--------------|-------------------|-----------------|---------|
| No            | Hybrid       | CFL          | 9-13W             |                 |         |

**Notes:**

1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.

2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.