

SeaTile® Natural Shell Series Installation and Care

SeaTile® Natural Shell Ceramic Back, Seamless or Mesh Back Tiles

- Install tiles carefully to avoid scratching with standard tile adhesives using white latex-modified thin set mortar for the bonding material and only non-sanded grout with minimal joints. Installation should be performed by experienced installers, familiar with the methods and guidelines set forth by The American National Standards Institute (ANSI).
- Use only non-abrasive and non-corrosive cleaning agents such as soap and water.
- Load bearing waterproof membranes are recommended in wet locations such as baths and showers.
- After Care: wash down with warm water – spills of staining liquids such as wine, juice, coffee, etc. should be cleaned immediately with warm water and liquid detergent.
- *All tiles should be installed in the same direction.*

Finishing: SeaTile® Ceramic Back and Laminate Natural Shell series are already coated with a special marine grade polyurethane so it is not necessary to recoat. Please consult with manufacturer if additional coatings are required.

Product Support: SeaTile® products are supported by brand name national companies. Please consult Matrix Z's technical department, or product representative for further recommendations and/or brand name products for use in the installation. Please refer to our web site www.matrix-z.com for further information. Please call or e-mail us at info@matrix-z.com for specific questions about our products.



www.matrix-z.com