

LED Pendant Chandelier Light Swirl Shape



Application: Perfect dining room, kitchen island, stairwell and more residential or commercial pendant lighting

Specifications

Model	A
Wattage	30W
Dimming	Triac Dimming
Lumen Output	2600 LM
Input Voltage	120Vac 60Hz
CCT	3000K-4000K-5000K Selectable
CRI	Ra>80
Working Temperature	~32°F ~+113°F / ~0°C ~+45°C
Environment Location	DAMP LOCATIONS
Finish	Chrome
Life Span	Lumen Maintenance over 70% @ 50,000+ Hours
Pendant Cable Length	Max at 5FT
PCS/BOX	1
Master Box Dimension	515x515x225MM / 20.27"x20.27"x8.85"
Master Box Weight	4.78LB

Certification



Feature

- **Uniform Illumination:** Frosted extruded diffuser provides smooth, evenly distributed light with reduced glare.
- **Selectable CCT:** 5CCT selectable design allows users to choose the appropriate color temperature for various applications and environments.
- **Smooth Dimming:** 10%–100% Triac dimming provides flexible light-level control and enhanced user comfort.
- **Durable Construction:** Aluminum housing with a flexible composite diffuser offers reliable performance and a clean, modern appearance.
- **Damp Location Rated:** Suitable for use in damp locations and a variety of indoor applications.

Dimension

