



General Information

Material number	
Type	ceiling light
Product segment	Indoor
Theme	sonstige / nicht zuordenbar

Dimensions

Article Height (in mm)	60
Article Width (in mm)	150
Article Length (in mm)	1210
Net Weight (in kg)	0.7 Kilogram
Article Diameter (in mm)	340
Base Diameter (in mm)	645
Article Overhang (in mm)	75
Canopy Height (in mm)	20
Canopy Diameter (in mm)	310
Canopy Length (in mm)	710
Canopy Width (in mm)	48
długość podstawy(w mm)	70
Szerokość podstawy (w mm)	70
Installation Depth (in mm)	40
Cutout (in mm)	80

Material & Colour

Enclosure Material	plastic, steel
Enclosure Colour	black
Glass/Shade Material	plastic
Glass/Shade Colour	white
Cable Colour	transparent

Functionality

Switch Type	without switch
Battery	No
Function	remote control incl. LED not replaceable control via remote control CCT
Kąt czujnika (in °)	150
Czułość min. (w lux)	10
Czułość maks. (w lux)	200
Burning Time min. (in sec.)	5
Burning Time max. (in sec.)	900
Distance (in Meter)	12
Battery Type	AAA; R03P; 1,5V

Technical Information

Protection Degree	IP20
Protection Class	1
Mains Voltage	220-240V,50/60Hz
Operation Voltage	220-240V,50/60Hz
max. Wattage (1)	14,6W
Dimmable	No
max. Wattage (2)	1X18W

Illuminant 1

Illuminant Type (1)	E27
Illuminant incl. (1)	Exclusive
Socket Type (1)	E27

Illuminant 1

Socket Type (1)	GU10
Illuminant Type (1)	GU10-LED
Illuminant incl. (1)	Inclusive
Energy efficiency class (EEI)	F
Info changeability□light source/driver	LED exchangeable by customers, no driver included

Illuminant 1

Socket Type (1)	LED
Illuminant Type (1)	LED
Illuminant incl. (1)	Inclusive
Lumen Complete	1600
Kelvin Complete	3000K
Light colour Complete	WARM WHITE
Energy efficiency class (EEI)	F
Dimmable	No
Info changeability□light source/driver	LED + driver cannot be exchanged
Nominal Lifetime (in h)	25000
Switching Cycles	15000
Rated Lamp Power (0,1W precision)	24,5
Colour Tolerance (LED, SDCM)	<6
lumen z osłoną	110

Illuminant 2

Socket Type (2)	LED
Illuminant Type (2)	LED
Illuminant incl. (2)	Inclusive
Lumen Complete	920;400
Kelvin Complete	3000K
Light colour Complete	WARM WHITE;WARM WHITE
Dimmable	No
Info changeability□light source/driver	LED + driver can be exchanged by a specialist

Illuminant 2

Illuminant Type (2)	E14-ILLU
Illuminant incl. (2)	Exclusive
Socket Type (2)	E14



14,6W 1600lm