



RUBBER CHOCK - PJ-4

*** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON









STANDARD FEATURES

MODEL NUMBER IS: PJ-4 OVERALL WIDTH IS: 2 1/4" USABLE WIDTH IS: 2 1/4" **OVERALL LENGTH IS: 4"** USABLE LENGTH IS: 4" OVERALL HEIGHT IS: 5 11/16"

SPECIAL FEATURES NONE

							-	CIAL UNITS RETURNABLE
			A P	-	I, the undersigned, hereby approve this print. This includes my approval of design & dimensions			
				P R		[] As	s drawn [] As marked
PLEASE CIRCLE SPECIFICATIONS					Si	gned:		Date:
	POWER AC DC (12V) AIR/OIL			Å		LEAD TIME WILL START UPON RECEIPT		
	MOTOR VOLTA	DR VOLTAGE 115 208 230 460			OF SIGNED APPROVAL DRAWING			
	DEDICATED CIRCUIT REQUIRED			DISTRIBUTOR'S NAME:				P.O.#
	MOTOR PHASE	OTOR PHASE SINGLE THREE CONTROL HAND FOOT		VESTIL MANUFAC			TURING	X
								W.O.# X
	CONIROL	HAND	FUUT	DRAWN BY	•	DATE:	COALE: 1.2	A SALES:
*	BATTERY CHRG.	REMOTE	ON-BOARD	M. BEII	ER	4/21/08	SCALE: 1:3	X
*	CHRG. INDICATOR	YES	NO	REFERENCE:			QUOTE #	FILE NAME:
* AVAILABLE AT ADDITIONAL COST				Х			Х	29-007-092

* AVAILABLE AT ADDITIONAL COST