

# WAC LIGHTING

## Disc 5CCT

### Ceiling and Wall Mount

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
FM-306 6"	9CS 2700K/3000K/3500K/4000K/5000K - 90	15W	950	WT White

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Example: **FM-306-9CS-WT**

#### DESCRIPTION

Multiple mid-powered LEDs uniformly illuminate the acrylic diffuser.

#### FEATURES

- Multiple LED array for uniform illumination
- 5-CCT Switchable between 2700K and 5000K
- ACLED driverless technology
- 5 year warranty

#### SPECIFICATIONS

<b>Construction</b>	Die-cast aluminum with white acrylic diffuser
<b>Power:</b>	15W
<b>Input:</b>	120 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-5% , TRIAC: 100-5%
<b>Light Source:</b>	Integrated LED
<b>Lens:</b>	Translucent acrylic diffuser
<b>Rated Life:</b>	50,000 Hours
<b>Mounting:</b>	Retrofit over a 5" or 6" recessed can or install over a 3" or 4" junction box, Can be mounted on ceiling or wall in all orientations
<b>Finish:</b>	Electrostatically Powder Coated: White
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Wet Location Listed, ADA, Title 24 JA8 Compliant




#### FINISHES:



White

#### LINE DRAWING



FM-306