




Instructions


NOTE :

1. Please Check whether the accessories are missing in time after unpacking. (Bulbs not included)
2. We offer 12 months guarantee. If you find any damaged or missing parts in transit, please feel free to contact us , we will solve it as soon as possible.

Wire connector




01




05



Screw the Mounting Bracket to the ceiling or junction box . (There are many gaps, you can screw it to the ceiling.)



If you install the Mounting Bracket into the electrical box, please use F to fix it instead of E.




04



03 Adjust the length

02




06

Fixture wires should be connected to ceiling wires by color, black wire to be attached to the black wire, white to white and ground wire to ground wire.




For your safety, you should use wire connector A or B as you like, if you choose connector A, you need to use Electric tape for it. If you choose connector C, you need to use heat gun for heating.




Fix the light to the ceiling

Wiring Instruction

T1




Wire nuts



Crimp terminal

T2




T3



T1

Wire nuts




Tips:

Screw the twisted electric wire completely into the terminal until it does not loosen.

T1

Crimp terminal




*** Pliers not included.***

Tips:

Use crimping pliers to ensure the wire are fastened to the terminal.

T2




*** Screwdriver not included.***

Tips:

Loosen the small screw, insert the wire, and tighten the screw.

T3



*** Heat gun NOT included.***

Tips:

1. Hold the heat gun about 3~6 inches away from the tubing, and keep it moving back and forth.
2. Continue heating the tubing until it is tightly secured to the wire.