



Project/Job Name:

Location:

Fixture Type:

Notes:

S11293 - 9 Watt; LED Gimbaled Downlight; 4 Inch; RGB & Tunable White; Round; Starfish IOT; White Finish; 650 Lumens; 120-277 Volt

- Air Tight
- Has Driver
- IOT Enabled
- CCT Selectable
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	9W
Volts:	120V-277V
Lumens:	650L
CRI:	90
CCT (Kelvins):	2700K-5000K
Color Description:	Warm to Cool White/Color Changeable
Beam Spread :	36
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	Only with Starfish App
Incandescent Equivalent :	50W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Replaceable Light Source :	No
Number of LEDs :	24
Connection:	Direct Wired
Power Factor :	>0.9
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923112935
Each Quantity:	1
Each Dimensions:	5.16 x 3.19 x 5.08
Case UPC:	10045923112932
Case Quantity:	12
Case Dimensions:	11.02 x 10.24 x 11.02

PHYSICAL

Finish:	White
Lens Finish:	Frost
Lens Material:	Plastic
Finish Family:	White
Dimensions:	H:1.44" DIA:4.92"
Weight (Lbs.):	0.99
Material:	Aluminum

INSTALLATION

Ceiling Aperture:	4.25 in. Cutout
Max Drywall Thickness:	1 in.
Rec. Spacing Between Fixtures:	3 ft. to 4 ft.
Clearance Height:	3

IOT

IOT Enabled:	Yes
What's Supported:	Google Home;Alexa;Siri;SmartThings

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2470769
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP42
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

INFO

Specification Note:	360 degree rotation; 0 to 80 degree aiming angle
---------------------	--

ACCESSORIES

	80-943	New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/ Joist mounting of 4-inch Recessed Downlights; Up to 4.25-inch hole diameter
	80-946	4" Goof Ring for Remote Driver Installation
	80-949	6 FOOT REMOTE DRIVER 1-PIN EXT
	80-950	New Construction Mounting Plate for Stud/ Joist mounting of 4-inch Recessed Downlights; Up to 4.563-inch hole diameter
	86-216	Temporary work light; LED; For use with remote drivers; Low voltage 10W/12W/24W; 3000K; 12 Volts