


Project:

## Light Frames Up/Down LED Sconce Spec Sheet

SKU: 7204.72-WL Learn more at:  
<https://sonnemanlight.com/light-frames-up-2fdown-led-sconce>

Description: LED illumination is directed downward from the interior top edge of the frame within a broad rectilinear column. Also available as a [Sconce](#) and [Bollard](#).

Type #:



### Dimensions

Height:	21"
Width:	7"
Extends:	2.5"
Minimum Extension:	2.5"
Maximum Extension:	2.5"
Size:	21"
Canopy/Backplate/Base Depth:	6.5
Canopy/Backplate/Base Height:	4.5

### Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Input Voltage:	120-277VAC
Wattage:	29
Initial Lumens:	3710
Delivered Lumens:	1550
Color Temperature:	3000K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	1
Power Supply Location:	Canopy
Dimming Type:	TRIAC & ELV @ 120V / 0-10V
Bulb Max Wattage:	29

### Installation

Installation:	Licensed electrician required
Installation Orientation:	Vertical

### Shipping

Carton 1 L x W x H:	23" X 9" X 5"
Carton 1 Gross Weight:	7 LBS
Fixture Weight:	5

### Shade

Shade 1 Material:	Aluminum
-------------------	----------

### Available Finishes

Available Finishes: Textured Bronze (.72), Textured Gray (.74), Textured White (.98)

### General Listings

Features:	Wet Rated
Certification:	cETL
Color/Finish:	Textured Bronze (.72)
Dark Sky Friendly:	N