STONE LOOK



XTERIORS™

ALL-WEATHER SOLUTIONS FOR EXTERIOR STYLE

BY daltile

COURIER™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

TREAD™

PORCELAIN PAVERS

COURIER™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

Three warm shades modernize the ancient character of limestone in this outdoor TREAD™ pavers series, Courier. With a design distinguished by its natural and minimal patterning, and a versatile selection of sizes, this series brings contemporary taste in a 2cm paver. Courier's soft aesthetic pairs effortlessly with any style to offer a sleek, sophisticated touch.

STONE LOOK

USAGE

- FLOOR
- WALL
- COUNTERTOP
- SHOWER FLOOR
- EXTERIOR FLOOR

SPECIAL FEATURES

- STEPWISE™
- TRU-EDGE™
- REVEAL SYNC3D™
- MADE IN THE U.S.A.
- LARGE FORMAT
- MOSAIC/ DECO
- ENCAUSTIC
- TERRAZZO
- PAVER
- CUSTOMIZE

PC COLORBODY PORCELAIN

LOW — HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

TAKE IT OUTSIDE

XTERIORS BY DALTILE

Cover and above photo feature Lookout, 24 x 24 2cm pavers on the patio floor.

STONE LOOK

COURIER™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

SIZES:

- 48 x 48 Paver Tile
- 32 x 32 Paver Tile
- 24 x 48 Paver Tile
- 24 x 24 Paver Tile
- 14 x 15 Foglie Mosaic Tile
- 12 x 11.5 Mosaic Blend Tile

FINISHES: TEXTURED | MATTE

24 x 48 COLORBODY™ PORCELAIN PAVERS



LOOKOUT CR90



ROCKWELL CR91



RIVER CR92

24 x 24 COLORBODY™ PORCELAIN PAVERS



LOOKOUT CR90



ROCKWELL CR91



RIVER CR92

14 x 15 FOGLIE MOSAIC TILE

LOOKOUT CR90



ROCKWELL CR91



RIVER CR92

12 x 11.5 MOSAIC BLEND TILE



MIXED RIVER CR93

50% MORE SLIP RESISTANT THAN ORDINARY TILE†

†When compared to tile meeting ANSI standards.

WATERPROOF

STAINPROOF

DENTPROOF

SCRATCH-RESISTANT

FIRE-RESISTANT†

†Not Applicable to Mesh-Mounted Mosaics

INDOOR/OUTDOOR

SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

COURIER™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

STONE LOOK

SIZES

		Thickness	Finish	Made in U.S.A.
48 x 48 Paver Tile***	47-3/16" x 47-3/16" (120.00 cm x 120.00 cm)	13/16" (2cm)	T	
32 x 32 Paver Tile**	31-1/4" x 31-1/4" (79.50 cm x 79.50 cm)	13/16" (2cm)	T	
24 x 48 Paver Tile	23-5/8" x 47-1/4" (60.00 cm x 120.00 cm)	13/16" (2cm)	T	
24 x 24 Paver Tile*	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	13/16" (2cm)	T	✓
14 x 15 Foglie Mosaic Tile**	13-7/16" x 14-15/16" Sheet (34.20 cm x 38.00 cm Sheet)	3/8"	M	
12 x 11.5 Mosaic Blend Tile**	12-1/125" x 11-13/16" Sheet (30.50 cm x 30.00 cm Sheet)	3/8"	M	

Made in the U.S.A. designation is subject to change. Please visit daltile.com for the most current manufacturing information.

T Textured Finish M Matte Finish

* Stepwise available in 24 x 24 only.
** Available as special order only.
*** Available as special order in CR90 and CR91 only.

TRIM†

	Type
	Step Nose Tile
	Coping Tile

† Trim items available in many sizes and colors. Consult with your sales representative and/or design team for specifics.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓*
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* Paver tile only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" orgreater in a staggered brick-joint pattern.) **Mosaic Tile:** 1/8"	Medium (V2)

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 0.5%
Breaking Strength	C1505	> 2000 lbf	> 275 lbf
Scratch Hardness	C1895	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant
Abrasion Resistance	C1027	N/A	N/A

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.3 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors,

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

PRE-CONSUMER RECYCLED MATERIALS **REVEAL IMAGING®**

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

CERTIFIED PORCELAIN TILE 0.5% or less water absorption

ZEROTOX

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at **daltile.com.**

daltile®

©2026 Daltile (07/26)