

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact: \_\_\_\_\_

Ceiling mounted • Dry location listed



## Description:

This five-blade 54" ceiling fan combines a frosted linen glass shade with a 17W LED source. This fan features a dual mount system and a three-speed pull chain fan switch, as well as an on/off pull chain switch to operate the light. LED light kit features a 3000K color temperature. Can be used to comply with California Title 20. Can be used to comply with 2016 Title 24 JA8.

## Specifications:

- Brushed Nickel (Plated)
- Steel construction
- Frosted linen glass Bowl
- The light kit contains a frosted linen glass shade and is comprised of a 17W dimmable 3000K LED module, offering 1400 lumens, 90+ CRI
- This fan features a dual mount system and a three-speed pull chain fan switch, as well as an on/off pull chain switch to operate the light.
- Indoor ceiling fan ideal for use in great rooms, living rooms, bedrooms and bonus rooms
- This fan features a dual mount system to offer greater flexibility when installing. The fan can be installed on a flat or sloped ceiling
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- Reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- Add a wall control or remote control for added convenience.
- Ceiling mounting on downrod
- A 3/4" x 6" downrod is included. Longer accessory downrods can be ordered separately
- Can be used to comply with California Title 20.
- High Speed Energy Information: Airflow- 4444 cfm, Energy consumption- 64 watts (excluding lights), Airflow efficiency- 79 cfm/watt
- Limited lifetime warranty.
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 80" of wire supplied
- Medium Cherry/American Walnut reversible blades, plywood construction
- Chrome pull chain with Maple fob
- 12 degree blade pitch
- Meets California Title 24 JA8-2016

## Performance:

Number of Modules	1
Input Power	18w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1386/77 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
EMI/RFI	Title 20
Min. Start Temp	-10 °C
Max. Operating Temp	40 °C
Warranty	Limited Lifetime warranty
Labels	UL Dry location listed
	Meets California Title 24 JA8-2016


## Images:



## Dimensions:

Diameter: 54"

Height: 16-5/8"





### Dimming Notes:

---

This fan is designed to be compatible with many controls.

The following is a partial list of known compatible dimmer controls.

### Dimming Controls

---

Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron - Caseta Wireless

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton - AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.