


HR-2LED-T709

2" Tesla™ LED Open Reflector Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, square downlight trim with interior open reflector

FEATURES

- 2" aperture
- CEC Title 24 Compliant (see below for list of models)
- Damp location listed
- 30° visual cutoff angle for glare control
- 90,000 hours rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Light Source: Utilizes one 14.5W LED, CRI: 85 & 90+

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing

Finish: White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

Standards: ETL & cETL Listed

See table below for California Title 24 Compliant for qualifying products.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	2013 Title 24	Finish
HR-2LED-T709 Open Reflector	S 15°	27 2700K	85	543	2886	No	BN Brushed Nickel CB Copper Bronze WT White
		W 3000K	85	587	3227	No	
		9W 3000K	90	659	3097	No	
		35 3500K	85	616	3374	No	
		C 4000K	85	520	3718	No	
	N 26°	27 2700K	85	536	1467	No	
		W 3000K	85	572	1598	No	
		9W 3000K	90	570	1512	Yes	
		35 3500K	85	601	1694	No	
		C 4000K	85	544	1638	No	
	F 45°	27 2700K	85	589	814	No	
		W 3000K	85	575	802	No	
		9W 3000K	90	515	596	Yes	
		35 3500K	85	589	814	No	
		C 4000K	85	560	994	No	

HR-2LED-T709



-



-



Example: HR-2LED-T709F-9W-BN

COMPATIBLE HOUSINGS

 See individual housing spec sheets for complete information.

Model	Input	Notes
HR-2LED-H09D-ICA	New Construction IC-Rated, Airtight	120V -277V Ceiling thickness: ½" –¾"
HR-2LED-H09D-ICAC	New Construction IC-Rated, Airtight Chicago Plenum	
HR-2LED-R09D-A	Remodel Non-IC, Airtight	Requires 3" of clearance from insulation on all sides 120V -277V Ceiling thickness: ½" –1"

REPLACEMENT MODULES

Reflectors

Spot
Narrow Flood
Flood

SL-REF-LUX10-S
SL-REF-LUX10-N
SL-REF-LUX10-F

LED

2700K	85 CRI	LXS8-PW27
3000K	85 CRI	LXS8-PW30
3000K	90 CRI	LXS9-PW30
3500K	85 CRI	LXS8-PW35
4000K	85 CRI	LXS8-PW40

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760