



1. Insert the lamp cap tube into the hole of the chip (pay attention to protect the lamp cap wire from being damaged)
2. Screw the lamp cap tube on the back of the chip with nut gasket
3. Connect the lamp cap wires of the same color with the wires of the same color of the lead wires
4. Cover the semicircle under the piece
5. Twist the nut on the exposed tooth canal under the semicircle
6. Pass the main line through the suspender, and then twist the suspender to the iron piece on the element
7. Twist the lifting ring onto the boom
8. Buckle the movable buckle into the lifting ring, and then tighten the movable buckle
9. Fix the hanging plate to the junction box with the screws on the accessory package
10. Connect the main line on the ceiling plate with the wire reserved on the ceiling with the wiring cap
11. Cover the whole lamp to the hanging plate (let the hanging plate screw expose the ceiling plate)
12. Screw the flower branch screws onto the exposed hanging plate screws
13. Insert the cap tube into the cap
14. Twist the bulb into the cap

Attention:

1. Please cut off the power supply before installation to prevent electric shock (installation by certified electrician is recommended)
2. Due to the different display, the actual color can be different from the image
3. Due to the manual measurement of lamp body size, there may be a deviation of 1 / 2 inch
4. If you have any questions or lost parts, please feel free to contact us and we will try our best to help you