

TRITOUR



Model: 109LPC44MBKMBK/109LPC44MWHMWH
 109LPC44BNSLV/109LPC44MBKDB
 109LPC52MBKMBK/109LPC52MWHMWH
 109LPC52BNSLV/109LPC52MBKDB



Brushed Nickel/Silver



Matte Black



Matte Black /Dark Wood



Matte White



Key Features & Benefits

- ABS Blades with Solid Finishes and Sleek Minimalist Design
- Pull Chain
- AC Motor and ETL listed
- Lifetime motor warranty

SOFT WHITE (3000K)

BRIGHT WHITE (4000K)

DAYLIGHT (5000K)

Product Specifications

Fan Size in Inches and Mounting Type

44"/ Downrod mount only, Flat or Angled ceiling (max. 18 degree)
 52"/ Downrod mount only, Flat or Angled ceiling (max. 18 degree)

CFM (High)

2986
 4237

Motor Type (AC, DC)/Size

AC / 153x12

Indoor/Outdoor/Finish

Indoor Only

Reversible, Blade Finish

Non-Reversible
 Available in Faux Wood (Dark Brown) and Solid Matte Black, Matte White and Silver

Damp or Wet Rated

Dry Rated

Lead Wire

54"(to allow 48-inch down-rod sold separately)

Blade Arms

N/A

Remote Control (Y/N)

N

Distance from ceiling to bottom of the light kit once installed
 14.58"

Distance from Ceiling to bottom of blade once installed (inches)
 9.26"

No. of Blades/Blade Material
 3/ABS

Light Kit (Y/N)

Y (Cannot be installed without light kit)

Lens Type

PC

Type of Bulbs

LED Module
 (can be replaced)

Bulb Wattage

18W

For LED Only

Lumen Output (Raw/Fixture)

1368/1000

Lumens/Watt

56

Color Temperature / CRI

3000K/4000K/5000K/≥90

LED Chip Brand

BRIDGELUX

Driver Module (AC or DC)

AC

