

ROOF INSTALLATION INSTRUCTIONS

*2 people are recommended for this step. If unit is being Installed against a structure, install post caps to the top of the posts prior to installing the roof. (See Instructions #10).

- a. Assemble the roof on the ground by starting with an end rail (side with openings facing upward) then place middle rails on top (middle rails have openings on both sides). Ensure the slants are facing the same direction as the first one. Install the pickets into each slot as in the picture (See Pic. 9a) Once they are all in place secure the remaining end rail into the pickets snapping them in.
- b. If you are using the pergola end caps it is important to use silicone or PVC cement to secure them to the cross beams in the front of the shower (door side). Secure the flat caps with silicone to the back side of the cross beams.

Pic. 9b





Single Roof Installation



Double Roof Installation







- c. With one person standing inside the shower to guide and support the roof, lift the roof, and slide it into place. (See Pic. 9c) Make sure the back of the cross beams are flush with the base frame before proceeding. The end cross beams should sit just inside your top post brackets. (See Pic. 9d) Dependent on unit size, space the center cross beams evenly. (See Pic. 9b)
- d. Use the L brackets and white self-drilling ¾" stainless steel screws to attach each cross beam to the inside of a wall panel or header on both the front and rear of the shower. (See Pic 9d)
- e. It is time to secure the privacy bar on either side of the roof rafters. Center the long side of the privacy bar between posts. Using Qty. (4) of the #8 self-drilling stainless steel screws for the 46" Units and Qty. (3) of the stainless steel screws for the 36" Units, space screws evenly across the bar and secure. (See Pic. 9e)
- f. For Solid Roof Installation place the PVC sheet on top of the support beams. Use the Stainless 1" self-drilling steel screws to secure the roof. (See Pic. 9f)







