



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11647 - 10 Watt LED High Output Downlight Retrofit; 4 Inch; 27K/30K/35K/40K/50K CCT Selectable; Round; White Finish

- Air Tight
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	10W
Volts:	120V
Lumens:	820L
CRI:	90
Rg Value :	50
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	100
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 120V only
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Phase cut
Incandescent Equivalent :	65W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Replaceable Light Source :	No
THD:	<30%
Power Factor :	>0.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923116476
Each Quantity:	1
Each Dimensions:	5.63 x 2.36 x 5.63

PHYSICAL

Finish:	White
Lens Finish:	Matte Frosted
Lens Material:	Polycarbonate (PC)
Dimensions:	H:1.86" DIA:5.12"
Weight (Lbs.):	0.27
Material:	Aluminum

INSTALLATION

Ceiling Aperture:	4.06 in. Cutout
Sloped Ceiling Compatible:	No
Can Size:	4 in.

COMPLIANCE

Safety Listing:	cULus - Classified; cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-3722188
Energy Star Lamp Category:	Downlight Solid State Retrofit
CA Prop 65:	Lead
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

**80-868**QC to E26 Socket Whip for Downlight Cans; Temp Light Adapter Cable

**80-980**4 Inch Recessed Can; For New Construction

**80-981**4 Inch Recessed Can; For Remodeling

**S8999**GU24 Socket Adapter For Recessed Down Light

**S9000**GU10 Socket Adapter For Recessed Down Light
