

MOTOR FINISH



BLADE FINISHES

Matte White, Silver



Dimmable



LED Light Kit



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	RPM Revolutions Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt	CFM (Low)	1655
4335	150	52	83	RPM (Low)	55
				Watts (Low)	12

SPECIFICATIONS

Light Source			
Dimmable	Yes	Downlight Included	Yes
Downlight Option	Integrated	Lamp Included	Integrated
Light Source	LED	# of Bulbs/LED Modules	1
Watts (High)	52	Watts (Low)	12
Photometrics			
Color Rendering Index	90	Delivered Efficacy (Lumens/Watt)	80
Kelvin Temperature	3000K		
Electrical			
Amps (High)	0.44	Amps (Low)	0.19
Motor Size	153MM X 20MM	Motor Type	AC Induction
Supply Wire (Degrees)	90		
Dimensions			
Base Backplate	6.00 DIA	Downrod 1	1.00" OD X 4.50"
Downrod 1 - Measurement A	14.75"	Downrod 1 - Measurement B	10.50"
Downrod 1 - Measurement C	8.75"	Weight	19.70 LBS
Mounting/Installation			
Minimum Distance from Fan to Floor	7.0 feet	Interior/Exterior	Interior
Lead Wire Length	78"	Location Rating	Dry
Low Ceiling Adaptable	No	Mounting Style	Downrod
Mounting Weight	17.60 LBS		

FIXTURE ATTRIBUTES

Product/Ordering Information			
SKU	300059MWH	Finish	Matte White
Style	Transitional	UPC	783927000024

Housing			
Diffuser Description	Etched Cased Opal	Primary Material	STEEL
Max Stem Tilt	22 Degrees	Remote Included	Yes
Blade Finish & Specs			
Blade Finish 1	Matte White	Blade Finish 2	Silver
Blade Material	PLYWOOD	Blade Pitch	12
Blades Included	Yes	Blade Sweep	52
Number of Blades	5	Blades Reversible	Yes
Warranty			
www.kichler.com/warranty			

ALSO IN THIS FAMILY



300059BSS



300059SBK

You can see all products in this family by searching **Kichler.com**