

BLACK JACK®

FLOATING FLOOR CUSHION UNDERLAYMENT



ADVANCED MOISTURE PROTECTION

The closed-cell foam design is moisture resistant



MOLD DEFENSE

Dense structure offers mold and mildew protection



SUPERIOR SOUND REDUCTION

Excellent sound reduction under laminate and engineered flooring.
IIC 70, STC 66, DELTA IIC 21




RADIANT HEAT

Ideal for radiant-heated floors with R-Value 0.425



CUSHIONING

2.5 mm foam layer and anti-crush technology provide optimal cushioning



EASE OF INSTALLATION

Adhesive strip and 3" overlap film join pieces and help provide a moisture barrier



Superior Cushioning & Sound Control

The ROBERTS® Black Jack® Floating Floor Cushion Underlayment is designed for use under floating laminate, bamboo and engineered wood floors, and is ideal for many types of subflooring. Black Jack is engineered as a superior grade 2.5 mm foam underlayment that provides optimal cushioning and sound absorption, as well as a closed-cell design that offers excellent moisture vapor resistance. For added convenience, this underlayment features a 3" overlap film and adhesive strip to join pieces and seal out moisture.

PRODUCT RATINGS*

IIC
70

STC
66

Δ Delta IIC
21

R-Value
0.425



BLACK JACK®

FLOATING FLOOR CUSHION UNDERLAYMENT



PRODUCT RATINGS*

IIC
70

STC
66

Δ Delta IIC
21

R-Value
0.425

SPECIFICATIONS (+/-10%):

Material Composition	Dense, closed-cell foam with a 3" overlapping film
Thickness	2.5 mm
Compression Set	ASTM – 4.4
Compression Strength	ASTM – 3.6 PSI
Indentations	ASTM F1914 - 0.019" at 50lbs
Smoke Density	ASTM E662 - PASS
Thermal Resistance (R-Value)	0.425
Water Vapor Permeance	ASTM E96 - 0.149 lbs/1000 ft²/24 hrs
Installation Methods	Floating
Warranty	Limited-Lifetime Warranty

AVAILABILITY (ROLL SIZES):

Item #	70-026	70-026-XL
Roll Size	100 ft² (9.3 m²)	600 ft² (55.74 m²)
Roll Width	43" (1.1 m)	43" (1.1 m)
Roll Length	28' (8.53 m)	167.5' (51.05 m)

Applications:

Residential & commercial

Approved Substrates:

Cured concrete, interior plywood and properly prepared OBS (skim coat may be required)

Approved for Use Under:

Laminate, bamboo and engineered wood flooring

Locations:

Below-grade, on-grade, & above-grade

