



# Persuade® Curv | K-6355

Two-piece elongated toilet with skirted trapway, dual-flush

## Features

- Two-piece design
- Elongated bowl offers added room and comfort
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults
- Top-mount two-button flush offers a choice of 1.0 or 1.6 gallons per flush (gpf)
- Skirted trapway simplifies cleaning
- Combination consists of toilet bowl and tank
- Dual-flush technology allows you to choose between a full or partial flush
- Patented ReadyLock® installation system, a simple solution for skirted toilets, saves time, hassle, and eliminates the need to drill into the floor for standard 12" (305 mm) rough-in
- Eligible for consumer rebates in some municipalities
- This product can help a building earn Water Efficiency points in LEED® Green Building Rating System
- Standard 12" (305 mm) rough-in only. Cannot be combined with K-5383, or K-5381 for use in 10" or 14" installations



## Sustainability



## Available Colors/Finishes

*Color tiles intended for reference only.*

|    |             |
|----|-------------|
| 0  | White       |
| 96 | Biscuit     |
| NY | Dune        |
| 95 | Ice Grey    |
| 7  | Black Black |



1-800-4KOHLER (1-800-456-4537)  
Kohler Co. reserves the right to make revisions without notice to product specifications.  
For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.  
8-13-2026 01:00 - US-CA

THE BOLD LOOK  
OF **KOHLER**

## Codes/Standards

*Accessibility standards may require controls to be located on the open side of the toilet.*

*Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.*



ASME A112.19.2/CSA B45.1

ASME A112.19.14

DOE - Energy Policy Act 1992

EPA WaterSense®

California Energy Commission (CEC)

## Recommended Products/Accessories

1265114 12" Toilet Supply Line

K-186 Dual-flush actuator

K-5588 Deodorizing elongated toilet seat

1362736 Mounting Plate Kit Exposed Wire

K-30780 Quiet-Close™ elongated toilet seat

## Warranty

*See website for detailed warranty information.*

KOHLER® Toilets and Seats Limited Warranty

## Technical Information

|                       |                                   |
|-----------------------|-----------------------------------|
| Rough-in:             | Standard 12" (305mm)              |
| Flush Type:           | Class Five                        |
| Flush Rate:           | 1.0 or 1.6 gpf (3.8 lpf)          |
| Bowl Shape:           | Elongated                         |
| Seat-Mounting Holes:  | 5-1/2" (140 mm)                   |
| Waste Outlet:         | Floor                             |
| Trapway Size:         | 2" (51 mm)                        |
| Trapway Type:         | Skirted                           |
| Water Surface Size:   | 4-1/2" x 5-3/4" (114 mm x 146 mm) |
| Rim to Water Surface: | 8-1/2" (216 mm)                   |

## Included Combo Skus

- K-3569 Toilet tank, dual-flush
- K-4326 Elongated toilet bowl with skirted trapway




1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.

8-13-2026 01:00 - US-CA



## Installation

- Seat sold separately
- Standard 12" (305 mm) rough-in
- Requires mounting plate for heated seat installation (sold separately)

## Installation Notes

*Install this product according to the installation instructions.*

The rough-in must be 12" (305 mm) or more from the base of the wall or baseboard. Install or relocate the supply and outlet as necessary to conform to rough-in dimensions.

If this toilet is installed in new construction, install a new supply stop following the dimensions in the diagram.

In installations with the supply stop installed, the existing supply stop may need to be relocated if it is less than 8-1/2" (216 mm) from the centerline of the toilet. Dry fit the toilet to confirm if the supply stop needs to be relocated.

The supplied hose will extend roughly 6" (152 mm) from the toilet. If the supplied hose does not reach the supply stop, a longer supply hose may be used.

For back-to-back toilet installations: Use only a 45° double wye fitting.

Product dimensions are nominal and may vary per ASME A112.19.2 tolerances.



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.

8-13-2026 01:00 - US-CA