

CONGRATULATIONS you have purchased a quality clock which plays the Westminster chime melody on the hour. Tolls the hour and has an automatic night shut-off (clock does not chime between 10:00 p.m. and 6:00 a.m.). To ensure that your clock functions correctly, please follow the time and chime setting instructions precisely. The clock will chime during the day and will automatically turn off at night.

INSTRUCTIONS:

TIME AND CHIME SETTING:

1. **BEFORE** inserting batteries set the clock at 6:05 AM (5 minutes past 6) with knob A.
2. Insert 1×AA Alkaline battery into the pendulum battery chamber.
3. Insert 1×AA Alkaline battery into the clock battery chamber, according to the positive (+) and negative (-) symbols.
4. Insert 2×AA Alkaline batteries into chime battery chamber, according to the positive (+) and negative (-) symbols. Make sure batteries are secure in the holder. The clock will chime automatically and toll 6 times.
5. Now turn hands (using knob A) slowly to the present hour (in a clockwise direction). Remember that the clock started at 6:05 in the morning. If setting at night, let's say, to 9:20 PM, then hands will be turned thus-7, 8,9,10,11,12,1,2,3,4,5,6,7,8,9 then 9:20 pm. The last strike you hear will be 9 times.

N.B. When moving hands to the present time clock will begin chiming. Do not be concerned about this. The last strike you hear after setting the clock at appointed time will be the correct one.

6. When replacing batteries remember that all the above must be repeated from point 1-i.e. the clock must be started again at 6:05 am. Therefore, please do not throw these instructions away as by the time the batteries have to be replaced; you may have forgotten how to set the clock.
7. To eliminate chimes, remove the two batteries from the Chime Battery Chamber.
8. Never turn clock hands counter clockwise as it will interrupt the chime sequence and damage the clock.

N.B. WHEN BATTERIES ARE LOW, CHIMES WILL NOT REMAIN CO-ORDINATED WITH THE TIME ON THE CLOCK. WHEN THIS HAPPENS, REPLACE WITH NEW ALKALINE BATTERIES AND RESET CLOCK AS ABOVE.

PENDULUM SETTING:

1. For transport security the small black plastic pendulum (B) may be attached to the case (at C) to prevent it from swinging.
2. At (D) using thumb pressure push towards your right to loosen the pendulum and allow it to swing freely.
3. Attach main pendulum to black pendulum at (E).
4. Give main pendulum a push sideways to get it swinging, place clock directly onto a strong hook on the wall and **ENSURE THAT THE BACK OF CLOCK IS FLUSH AGAINST THE WALL.**

N.B. The hook in the wall should not be too long so that the clock leans forward from the wall. The clock should hang on the hook with the back of the clock touching the wall to ensure stability in order for the pendulum to swing freely.

PLEASE ENSURE THAT THE CLOCK, THE MOTOR AND THE PENDULUM ARE ALL ALIGNED AND VERTICAL WHEN HANGING ON THE WALL.

