



Corbelle® | K-5711

ContinuousClean XT toilet tank, 1.28 gpf

Features

- 1.28 gpf (4.8 lpf)
- Left-hand Polished Chrome trip lever
- ContinuousClean system automatically dispenses cleaning solution with every flush
- Works with any white toilet bowl cleaner tablet. Tablets last up to one year in ContinuousClean XT system
- Combines with the K-4144 bowl to create a complete K-5709 Corbelle ContinuousClean toilet
- AquaPiston® canister optimizes the flow out of the tank, harnessing gravity and the natural, powerful reducing cascade of water to increase the power and effectiveness of the flush
- Easy-to-flush canister design requires less force to actuate than a 3" (76 mm) flapper, and has 90% less exposed seal material which resists conditions that cause wear, tear, shrinkage and swelling
- Optional: uses two AAA batteries (included) to power the LED system indicator light
- Adjustment dial lets you set how much cleaning solution is dispensed with every flush



Sustainability



Available Colors/Finishes

Color tiles intended for reference only.

0	White
96	Biscuit
NY	Dune
95	Ice Grey
7	Black Black



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

8-06-2026 17:11 - US-CA

THE BOLD LOOK
OF **KOHLER**

Codes/Standards

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.



ASME A112.19.2/CSA B45.1
EPA WaterSense®

Technical Information

Flush Type: AquaPiston
Flush Rate: 1.28 gpf (4.8 lpf)

Recommended Products/Accessories

K-20120-L Left-hand trip lever
K-23726 Drain treatment
K-4144 Elongated toilet bowl with skirted trapway

Warranty

See website for detailed warranty information.

KOHLER® Toilets and Seats Limited Warranty



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
8-06-2026 17:11 - US-CA

No image available.
This product is a component and not intended to be a standalone installation.

Installation Notes

Install this product according to the installation instructions.

Product dimensions are nominal and may vary per ASME
A112.19.2 tolerances.

