

Pull-Out Kitchen Faucet Installation Instructions

Step 1

Shut off the main water supply.
Remove old faucet and flexible hoses.
Clean sink surface with non abrasive
cleaner to prepare for new faucet

Step 2

Connect water lines to the bottom of the faucet.
Attach cold and hot water hoses to the faucet.
****Caution**** Do not over tighten the water
supply lines, this could cause leaks and
damage to the supply lines..

Step 3

Thread the water lines through the
mounting shaft and screw mounting
shaft into the bottom of the faucet until
the shaft is snug. Then unscrew mounting
nut and remove washer and mounting gasket.

Step 4

Position the faucet in the countertop hole.
From beneath the countertop hole, assemble
the rubber ring and metal washer and then
thread the metal nut onto bottom of faucet.
Tighten the metal nut until faucet is secure
and in the disired position. Tighten screws
for added support.

Step 5

Connect waterlines to water supply plumbing.
****Caution**** Do not over tighten the water supply
lines, this could cause leaks and damage to the
supply lines. Turn on water supply and check
for leaks. Adjust water connections as needed.

Step 6

Unscrew the spray nozzle on the faucet
and flush the faucet by running water
through the faucet without the head.
This will clear any debris that may be
inside the faucet. Reinstall the spray
nozzle to complete assembly.

Thank you for choosing Raen to be part of your home

