# QUICK REFERENCE GUIDE



# 2224ZWC • 24" Wine Captain® Model • 2000 Series



# **MODEL DETAILS**

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-2224ZWCS-00B	115 / 60	Field Reversible	Stainless Frame	160 lb
U-2224ZWCS-13B	115 / 60	Right-Hand Hinged	Stainless Frame (Lock)	160 lb
U-2224ZWCS-15B	115 / 60	Left-Hand Hinged	Stainless Frame (Lock)	160 lb
U-2224ZWCINT-00B	115 / 60	Field Reversible	Integrated Frame	157 lb
U-2224ZWCINT-60B	115 / 60	Field Reversible	Integrated Solid	150 lb

# ACCESSORIES

Model	Description	Finish	Shipping Weight
23074	Professional Door Handle, 1 1/4" Diameter	Stainless	2 lb
23073	Commercial Door Handle, 7/8" Diameter	Stainless	2 lb
U-ESPF60S*	Euro Style Handleless Panel, 24" Frame	Stainless	8 lb
U-ESP60S*	Euro Style Handleless Panel, 24" Solid	Stainless	12 lb

\*Installs on integrated models.

# **FEATURES & BENEFITS**







# 2000 Series • 24" Wine Captain® Model • 2224ZWC

#### DIMENSIONS

Dimensions shown apply to all finishes, including Integrated (INT) models with 34'' integrated panel/frame installed.



## **CABINET CUT-OUT**



# **INSTALLATION NOTES**

When installing adjacent to wall, ensure 2  $\frac{1}{2''}$  clearance on hinged side for 90° door opening, allowing ample room for door handle.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

# SPECIFICATIONS

Model	2224ZWC	
Amps: Running	1.2	
Capacity: Average Volume (cu ft)	4.7	
Capacity: Wine Bottle (750 ml)	43	
Control Type	Digital Touch Pad	
Dimensions: Product Depth	23 7⁄16" / 590 mm	
Dimensions: Product Height	33 <sup>11</sup> /16" / 856 mm	
Dimensions: Product Width	23 5⁄8" / 600 mm	
ENERGY STAR	N/A	
Panel Height	30" / 762 mm	
Panel Thickness	<sup>3</sup> ⁄4" / 20 mm	
Panel Type	2 <sup>3</sup> /4" / 70 mm Frame Panel or Solid Panel (-60 suffix)	
Panel Width	23 ½″ / 595 mm	
Product Weight: Max	150 lb	
Refrigerant Type	R600a	
Sabbath (Star K Certified)	Yes	
Temperature Range	34°F - 65°F	

## **COOLING SYSTEM**



# **ELECTRICAL REQUIREMENTS**

This unit requires a grounded, polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).



Please visit U-Line.com to view this model's User Guide. All specifications are subject to change without notice.