

## Specifications

Color: Silver

Style: Modern

Assembly Required: Yes

Plug Type: US Standard

Mount Type: Under-cabinet Mounted, Wall Mounted

Material: Cold-rolled Steel Plate, Glass, Stainless Steel

Process: Punching, Bending, Welding, Polishing, Wire Drawing, Spraying

Motor Type: Double AC Pure Copper Motor

Color Temperature: 6000K, Cold Light

Light Source: LED

Voltage: 110V/50Hz

Motor Power: 160W

Lamp Power: 2\*1.5W

Noise:  $\leq 56$ dB

Air Volume: 200m<sup>3</sup>/h, 350m<sup>3</sup>/h, 500m<sup>3</sup>/h

Air Outlet Diameter: 12cm/4.72in

Minimum Electrical Distance: 65cm/25.59in

Minimum Gas Distance: 65cm/25.59in

Number of Activated Carbon Filters: 2

Grease Separation Efficiency:  $\geq 85\%$

Glass Flap Length: 60cm/23.62in

Product Overall Size: 59.8\*49.5\*14cm/23.54\*19.49\*5.51in

Packaging Size: 64\*53.5\*18cm/25.2\*21\*7in

Gross Weight: 7.7kg/16.98lbs

Net Weight: 6.5kg/14.33lbs

## Notes

1. Please check the size carefully before ordering.
2. We recommend installing it about 27.56in away from the cooktop.
3. Please read the English manual and product label carefully before use and pay particular attention to the safety instructions contained therein.
4. Please allow the slight color difference caused by the shooting light and 1-3cm error due to manual measurement, and make sure you do not mind before you order.