

## Features

- Includes mirror defogging
- Dimmable LED task lighting to 1%
- Compatible with most Triac/Phase-cut dimmers
- Energy efficient LED lighting:

Kelvin	2700
CRI	90+
Lumens*	746-1488
Lux**	366
R9 Value*	50+
Foot-candles**	34
Watt Output - LED	42
Watt Output - LED with defogger on	78

\* Based on a measurement of subset of sizes, shapes and lighting styles  
 \*\* Measured at 18" from center of the mirror

## Construction

- Anodized aluminum back frame
- Quality polished edge mirror
- Power cords installed for easy plugin installation
- Constructed for surface mounting
- Includes installation hardware

## Codes/Standards Applicable

Vitality Mirror is UL certified to:


- UL 962
- CSA-C22.2, No. 12-82

## Dimensions

Height: 40" (1016 mm)

Width: 36" (914 mm)

Depth: 1-3/4" (45 mm)




## Model Number Key

Vitality	Mirror	Width	Height	Shape	Light Pattern	Edge Type	Options	Color Temp
Y	M	36	40	R = Rectangle	P = Perimeter	FP = Flat, Polished	D = Defogger	3 = 2700K

## Electrical System

- 120 Vac 60Hz (TBD) recessed wall outlet as shown in drawing



\* Defogger Size

† See instructions for wiring and location