



PERFORMANCE CHARACTERISTICS

TEST	STANDARD USED	MIN. REQUIREMENTS	RESULTS
Water Absorption	ASTM C373-18	≤0.50%	0.04%-0.09%
DCOF (Matte only)	ANSI A326.3-2017	≥0.42	0.54
Bending / Breaking Strength	ASTM C648	> 250 lbs	> 250 lbs
Chemical Resistance	ASTM C650-04	min.UB	Conforms
Frost Resistance	EN ISO 10545-12	Required	Conforms
Stain Resistance	ASTM C1378-04	>Class 3	Conforms

NOTE

Since there are variations in all fired ceramic and natural products, tile supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles prior to installation. Manufactured in accordance with ANSI A137.1 standards. Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

PACKING DETAILS

TILE SIZE	PC/BOX	SF/BOX	KGS/BOX	BOX/PALLET
1" Hexagon	20	16.79	16.00	54
2" Hexagon	20	19.73	20.20	54
1" Penny round	20	19.73	17.50	54
1"x3" Herringbone	20	18.83	20.00	54
Fish scale mosaic	20	19.10	21.00	54