Product Installation Instructions





Ax1



Bx1



Cx1



Dx1



Ex3



Fx1



Gx1



Hx1



Ix1

1		Three-in-one rod (10x38mm)	31pcs +4pcs
2		Eccentric wheel (12x15mm)	31pcs +4pcs
3		Non-slip pads	8pcs +4pcs
4		Magnetic Attraction & Screw (3x10mm)	2pcs 4pcs +1pcs
5		Hinge & Screw (4x10mm)	4pcs 8pcs
6		Screw (3.5x12mm)	16pcs +2pcs
7		Handle & screw (4x18mm)	2pcs 4pcs +1pcs
8	x2  x2  x2 (3.5x14mm) x4  x2 (4x45mm)	Anti fall hardware	
		Wire clamp	2pcs +1pcs
		AC/DC Adapter (12V⎓2.0A)	1pcs



1pcs



Double-head screwdriver, use as required

Product structure decomposition



Use parts ① and ②

Step1



Step2



Step3





Use a screwdriver to lock in the direction of the "+" sign



Disassemble along the direction of "-" sign

Step 1





Step 2





Step 3





Keep the side holes on the same side when installing

Step 4





Step 5





Step 6

2 x2

First thread the wire through the "D" plate



Step 7

2 x4



Step 8

2 x3



Step 9





Step 10

2 x13



Step 11

③ [redacted]

x8





Tear off release paper and stick the black foot pad on the board

12

Step 12





Step 13





Step 14



2 x4

Step 15

Be careful not to scratch your hand









Step 16

Be careful not to scratch your hand





Step 1



Step 2



Step 3

Step 17

6 x16





First lock the elliptical hole, then lock the fixed hole

17

Step 18



Turning this screw can effectively adjust the size of the door gap.



Turn this screw to adjust the door panel to be flat with the side panel.

Step 19

7 x2 x4



Step 20



Step 21



x2



x2



21

Step 22



x1



Step 23



8 x2 x2 x2



3.5x14mm



Install the anti fall hardware on the cabinet as shown in the picture first



Then mark the wall with a pen through the holes in the anti-fall hardware

Step 24



8 x2

x2 x2

Drill the hole with an electric drill and punch in the colloidal particles



4x45mm



Fasten the cabinet to the wall

User's Guide

Thank you for purchasing this product. To use this product, please plug it into a 12V DC power supply. Please use if the product works normally after connecting to power.

Introduction

The box is an intelligent controller with 2 touch buttons. It can turn ON/OFF the light, change light colors, and adjust the light luminance.

Product Show



ATTENTION PLEASE

1. If there is no touch response suddenly, Re-plug the power to reset the touch static electricity.
2. If bubbles appear on the panel, remove the protective film.

Operation

This touch button is used to turn on/off, change colors, and adjust brightness.

A. Short touch -> lighting on -> short touch -> change light color -> short touch -> change light color -> short touch -> lighting off. **B**. Long touch -> adjust the luminance

This touch button is used to turn on/off the induction function.

A. Short touch to turn on the induction function. It can auto-turn on the light when people are close to the controller in 1 meters. It can auto power off the light when the body is far away from the controller after 30 seconds.

B. Long touch to turn off the induction function.

C. Note: When you touch the light button to change the light modes, the induction function will automatically turn off. It is best to turn on this function after selecting the light color and adjusting the brightness you want.