



SENSBLE STRIPE EQ301

Specification

Product Type:	Carpet Tile
Construction:	Tufted
Surface Appearance:	Textured Patterned Loop
Gauge:	1/10" (39.37 rows per 10 cm)
Pile Weight:	14 oz/yd ² (474 g/m ²)
Pile Thickness:	.071" (1.80 mm)
Estimated Total Thickness:	.183" (4.65 mm)
Total Weight:	55.73
Stitches Per Inch:	9.8 (38.58 per 10 cm)
Dye Method:	Solution Dyed
Fiber Type:	Envirostrand® SD Nylon
Stain Release Technology:	N/A
Soil Release Technology:	EcoSentry Soil Protection
Density:	7,098
Weight Density:	99,380
Backing Materials:	EcoFlex Matrix
Installation Method:	Quarter Turn / Brick Ashlar / Multi Directional
Size:	24" x 24" (.6096 m x .6096 m)
Flammability:	ASTM E 648 Class I (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
IAQ Green Label Plus:	100055
NSF 140:	N/A
Warranties:	10 Year Limited Carpet Tile Warranty 10 Year Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants 10 Year Stain Warranty 10 Year Limited Static

All specifications are subject to normal manufacturing tolerances.

08/23