



General Information

| | |
|-----------------|-----------------------------------|
| Type | table light |
| Product segment | Indoor |
| Theme | sonstige / nicht zuordenbar |
| FSC® | FSC® Mix70% Hevea br FSC® C152762 |

Dimensions

| | |
|----------------------------|---------------|
| Article Height (in mm) | 475 |
| Article Length (in mm) | 560 |
| Net Weight (in kg) | 2.15 Kilogram |
| Article Overhang (in mm) | 120 |
| Article Width (in mm) | 180 |
| Article Diameter (in mm) | 595 |
| Canopy Length (in mm) | 145 |
| Canopy Width (in mm) | 28 |
| Canopy Height (in mm) | 41 |
| Base Diameter (in mm) | 180 |
| Base Length (in mm) | 180 |
| Base Width (in mm) | 180 |
| Installation Depth (in mm) | 26 |
| Cutout (in mm) | 205 |

Material & Colour

| | |
|----------------------|--------|
| Enclosure Material | steel |
| Enclosure Colour | black |
| Glass/Shade Material | fabric |
| Glass/Shade Colour | black |
| Cable Colour | black |

Functionality

| | |
|-----------------------------|---------------------|
| Switch Type | in-line switch |
| Battery | No |
| Function | LED not replaceable |
| Battery Type | CR2032 |
| Sensor Angle (in °) | 120 |
| Sensitivity min. (in lux) | 30 |
| Burning Time min. (in sec.) | 5 |
| Burning Time max. (in sec.) | 15 |
| Distance (in Meter) | 6 |

Technical Information

| | |
|-------------------|------------------|
| Protection Degree | IP20 |
| Protection Class | 2 |
| Mains Voltage | 220-240V,50/60Hz |
| Operation Voltage | 220-240V,50/60Hz |
| max. Wattage (1) | 1X40W |
| Dimmable | No |
| Spannung | 220-240V 50/60Hz |
| U out | 46-70V |
| I out | 300mA |
| Hz | 100Hz |

Illuminant 1

| | |
|----------------------|-----------|
| Illuminant Type (1) | E27 |
| Illuminant incl. (1) | Exclusive |
| Socket Type (1) | E27 |

Illuminant 1

| | |
|--|---|
| Socket Type (1) | LED |
| Illuminant Type (1) | LED |
| Illuminant incl. (1) | Inclusive |
| Kelvin Complete | 4000K |
| Light colour Complete | WHITE |
| Nominal Lifetime (in h) | 25000 |
| Switching Cycles | 15000 |
| Energy efficiency class (EEI) | E |
| Dimmable | No |
| Info changeability□light source/driver | LED + driver can be exchanged by a specialist |
| Rated Lamp Power (0,1W precision) | 36 |
| Colour Tolerance (LED, SDCM) | <6 |
| Lumen Complete | 1350 |

Illuminant 1

| | |
|--|---|
| Socket Type (1) | GU10 |
| Illuminant Type (1) | GU10-LED |
| Illuminant incl. (1) | Inclusive |
| Energy efficiency class (EEI) | F |
| Info changeability□light source/driver | LED exchangeable by customers, no driver included |



E27

1X40
W