


specifications:

1. Visible surface must be smooth and smooth, natural transition.
2. Against the wall must be vertical, the other several faces also try to vertical.
3. Make sure there is no water in the basin.
4. Can Not have acute angle, visible surface of the corner is R=2.
5. Positive and negative tolerance:2mm

			Size:1200*500*50mm		
Mark	Number of pieces	Change content	Signature	date	Proportion
Design		standardization			1 PCS 1
Revise		Check			
Technology		Approve			Total 1 PCS No. 1 PCS

TEXT5
 PHA
 HAT
 DIM
 HID.5
 HID
 CEN.5
 CEN
 DRW2
 DRW



BASIN DIMENSIONS (inch)

Sink Size	Length (from left to right)	Width (from front to back)	Depth (from top to bottom)	Distance between the side of the faucet hole and the back edge of the basin	Distance between the center of the faucet hole and the back edge of the top	Distance between the center of the drain hole and the back edge of the top	Distance between the center of the faucet/drain hole and closer side edge of the top	Distance between two faucet/drain holes (center to center)	Distance between the two basins
									
24" SINK	18	12	4	1.75	2.35	10.5	12	/	/
30" SINK	18	12	4	1.75	2.35	10.5	15	/	/
36" SINK	18	12	4	1.75	2.35	10.5	17.75	/	/
42" SINK	20	12	4	1.75	2.35	10.5	21	/	/
48" SINK	20	12	4	1.75	2.35	10.5	23.5	/	/
60"S SINK	24	13	5	1.75	2.5	9.25	29.5	/	/
60"SL SINK	20	12	4	1.75	2.35	10.5	14.75	/	/
60"SR SINK	20	12	4	1.75	2.35	10.5	14.75	/	/
60"D SINK	18	12	4	1.75	2.35	10.5	14.75	29.5	11.5
72"D SINK	20	12	4	1.75	2.35	10.5	17.75	35.5	15.75
84"D SINK	20	12	4	1.75	2.35	10.5	21	41.75	22

Faucet Hole: ϕ 1.2

Drain Hole: ϕ 1.75