




Arched Decor Safety Gate

Barrière Arquée Décorative de Sécurité

Puerta Decorativa Arqueada de Seguridad

Models / Modèles / Modelos: 0370BR, 0380BR



• READ ALL INSTRUCTIONS BEFORE ASSEMBLY AND USE OF GATE. KEEP INSTRUCTIONS FOR FUTURE USE.

• LIRE TOUTES LES INSTRUCTIONS AVANT D'ASSEMBLER ET D'UTILISER LA BARRIÈRE. CONSERVER CES INSTRUCTIONS POUR UNE UTILISATION ULTÉRIEURE.

• LEA TODAS LAS INSTRUCCIONES ANTES DE MONTAR Y USAR LA REJA. GUÁRDELAS PARA UTILIZARLAS COMO REFERENCIA.

www.regalo-baby.com


Regalo International, LLC.

3200 Corporate Center Drive, Suite 100 / Burnsville, MN 55306, USA / , É.-U. / , EE. UU.

866.272.5274 (U.S. only / aux États-Unis seulement / solo en EE. UU.) or / ou / o 952.435.1080

Made in China / Fabriqué en Chine / Hecha en China

Before Assembly



PLEASE CHECK TO MAKE SURE YOU HAVE THE FOLLOWING PARTS:

- | | |
|------------------------------------|--|
| A Left Side Frame Half (1) | F Wall Cups (4) |
| B Gate Door Panel (1) | G 1" Wall Mount Screws (4) |
| C Right Side Frame Half (1) | H Spring Loaded Upper Door Mounting Pin (1) |
| D 4" Extension (1) | I Frame Assembly Screws (2) |
| E Threaded Spindle Rods (4) | J Hex Key (1) |

NOTE

MODEL NO. MAX SIZE

0370	29 ↔ 35 in, ↑ 30 in tall
0380	29 ↔ 35 in, ↑ 36 in tall

BEFORE USING PRODUCT

Read and follow all instructions carefully to ensure that your gate and extensions are properly installed. Improper installation could result in the gate becoming unstable or dislodged from the doorway. Always make sure the extension is securely attached to the gate before using. The safety of your child is your responsibility. Please keep these instructions for your reference.

IMPORTANT

- Never use more than two extensions per side of gate.
- If hardware mounting to a surface other than drywall or wood, please consult with a professional about installation.
- Base locks are to be used at all times, on both sides of the gate.

REMOVING YOUR GATE FROM THE WALL


To remove your gate from the wall, rotate the adjustment wheels on each of the (4) threaded spindle rods to depressurize the gate from its doorway or opening. Then, gently pull or push the gate free from its doorway or opening.

CARE AND MAINTENANCE

Periodically check the gate for signs of damage, wear, or missing components. Do not use if any part is missing, worn or damaged. Check the gate regularly to ensure all the hardware and mountings are tightened. Do not use abrasive cleaners or bleach. Clean by sponging with warm water and a mild detergent.


Assembling and Installing Your Gate

STEP 1




Take the left (A) and right (C) gate frame halves and align the holes in the lower horizontal tube. Place the frame halves together and then using the frame assembly screws (I), tighten the two halves together.

STEP 2




Lower the gate door (B) into the assembled gate frame and insert the lower gate door pin into the mounting hole on the frame.

STEP 3




Align the hole in the upper corner of the gate door with the hole in the door mounting bracket. Insert the spring loaded mounting pin (H) into the hole in the mounting bracket and the door.

STEP 4




Locate the (4) threaded spindle rods (E). Rotate the adjustment wheels along the threading, eliminating the gap between the adjustment wheel and the rubber foot.

STEP 5




Insert the (4) threaded spindle rods into the holes at each of the four corners of the gate.

STEP 6




Position the gate so that it is level and centered within your doorway or opening. Rotate the adjustment wheels on the threaded spindle rods in the opposite direction as in Step 4, expanding the gap between the rubber foot and the adjustment wheel. Expand each of the (4) threaded spindle rods until they make contact with the doorway or opening. Do not fully tighten the threaded spindle rods yet.

STEP 7




When you are satisfied with the general placement of your gate, fully tighten the threaded spindle rods attached to the lower corners of the gate by further rotating the adjustment wheels. Continue by tightening the upper threaded spindle rods. As you tighten the threaded spindle rods, you will notice the gap between the door frame and the arched handle latch begin to narrow. In order for the gate to function properly, stop tightening the upper threaded spindle rods just before the outer housing of the arched handle latch and the receiving component touch.

STEP 8




NOTE: There should be equal spacing among each of the (4) threaded spindle rods. Make the appropriate adjustment to ensure you have installed your gate safely.

STEP 9




Position the gate so that it is level and centered within your doorway or opening. Rotate the adjustment wheels on the threaded spindle rods in the opposite direction as in Step 4, expanding the gap between the rubber foot and the adjustment wheel. Expand each of the (4) threaded spindle rods until they make contact with the doorway or opening. Do not fully tighten the threaded spindle rods yet.

STEP 10




With gate fully removed, you can now use the circles you marked during Step 1 as guides for screwing in your (4) wall cups. Center each of the wall cups within the guide circles and use the provided self-tapping screws (G) to fasten them in place via the hole through the center of each wall cup.

STEP 11




Reinstall your gate in the doorway or opening according to the instructions, using the newly installed wall cups as anchoring points for the (4) threaded spindle rods.

STEP 12




Remove the top and bottom threaded spindle rods. Assemble the gate and extension as illustrated. Reposition the gate and fit in accordance with the gate fitting.

STEP 13




NOTE: It is preferable to install any extensions on the hinge side of the gate.

STEP 14



Hardware Kit #11055 includes: Threaded Spindle Rods w/ Adjustment Wheel (4), Spring Loaded Upper Door Mounting Pin (1), 1" Wall Mount Screws (4), Frame Assembly Screw (2), Wall Cups (4), Hex Key (1).

STEP 15



90 DAYS LIMITED WARRANTY
If, during the first 90 days after consumer purchase of the item, under reasonable and non-commercial use and conditions of maintenance, it fails while owned by the original purchaser because of the quality of materials or workmanship of finish and assembly, Regalo International, LLC, will replace or repair it at Regalo's option. PROOF OF PURCHASE REQUIRED.




Arched Decor Safety Gate

Barrière Arquée Décorative de Sécurité

Puerta Decorativa Arqueada de Seguridad

Models / Modèles / Modelos: 0370BR, 0380BR



• READ ALL INSTRUCTIONS BEFORE ASSEMBLY AND USE OF GATE. KEEP INSTRUCTIONS FOR FUTURE USE.

• LIRE TOUTES LES INSTRUCTIONS AVANT D'ASSEMBLER ET D'UTILISER LA BARRIÈRE. CONSERVER CES INSTRUCTIONS POUR UNE UTILISATION ULTÉRIEURE.

• LEA TODAS LAS INSTRUCCIONES ANTES DE MONTAR Y USAR LA REJA. GUÁRDELAS PARA UTILIZARLAS COMO REFERENCIA.

www.regalo-baby.com


Regalo International, LLC.

3200 Corporate Center Drive, Suite 100 / Burnsville, MN 55306, USA / , É.-U. / , EE. UU.

866.272.5274 (U.S. only / aux États-Unis seulement / solo en EE. UU.) or / ou / o 952.435.1080

Made in China / Fabriqué en Chine / Hecha en China

Before Assembly



PLEASE CHECK TO MAKE SURE YOU HAVE THE FOLLOWING PARTS:

- | | |
|------------------------------------|--|
| A Left Side Frame Half (1) | F Wall Cups (4) |
| B Gate Door Panel (1) | G 1" Wall Mount Screws (4) |
| C Right Side Frame Half (1) | H Spring Loaded Upper Door Mounting Pin (1) |
| D 4" Extension (1) | I Frame Assembly Screws (2) |
| E Threaded Spindle Rods (4) | J Hex Key (1) |

NOTE

MODEL NO. MAX SIZE

0370	29 ↔ 35 in, ↑ 30 in tall
0380	29 ↔ 35 in, ↑ 36 in tall

BEFORE USING PRODUCT

Read and follow all instructions carefully to ensure that your gate and extensions are properly installed. Improper installation could result in the gate becoming unstable or dislodged from the doorway. Always make sure the extension is securely attached to the gate before using. The safety of your child is your responsibility. Please keep these instructions for your reference.

IMPORTANT

- Never use more than two extensions per side of gate.
- If hardware mounting to a surface other than drywall or wood, please consult with a professional about installation.
- Base locks are to be used at all times, on both sides of the gate.

REMOVING YOUR GATE FROM THE WALL


To remove your gate from the wall, rotate the adjustment wheels on each of the (4) threaded spindle rods to depressurize the gate from its doorway or opening. Then, gently pull or push the gate free from its doorway or opening.

CARE AND MAINTENANCE

Periodically check the gate for signs of damage, wear, or missing components. Do not use if any part is missing, worn or damaged. Check the gate regularly to ensure all the hardware and mountings are tightened. Do not use abrasive cleaners or bleach. Clean by sponging with warm water and a mild detergent.


Assembling and Installing Your Gate

STEP 1




Take the left (A) and right (C) gate frame halves and align the holes in the lower horizontal tube. Place the frame halves together and then using the frame assembly screws (I), tighten the two halves together.

STEP 2




Lower the gate door (B) into the assembled gate frame and insert the lower gate door pin into the mounting hole on the frame.

STEP 3




Align the hole in the upper corner of the gate door with the hole in the door mounting bracket. Insert the spring loaded mounting pin (H) into the hole in the mounting bracket and the door.

STEP 4




Locate the (4) threaded spindle rods (E). Rotate the adjustment wheels along the threading, eliminating the gap between the adjustment wheel and the rubber foot.

STEP 5




Insert the (4) threaded spindle rods into the holes at each of the four corners of the gate.

STEP 6




Position the gate so that it is level and centered within your doorway or opening. Rotate the adjustment wheels on the threaded spindle rods in the opposite direction as in Step 4, expanding the gap between the rubber foot and the adjustment wheel. Expand each of the (4) threaded spindle rods until they make contact with the doorway or opening. Do not fully tighten the threaded spindle rods yet.

STEP 7




When you are satisfied with the general placement of your gate, fully tighten the threaded spindle rods attached to the lower corners of the gate by further rotating the adjustment wheels. Continue by tightening the upper threaded spindle rods. As you tighten the threaded spindle rods, you will notice the gap between the door frame and the arched handle latch begin to narrow. In order for the gate to function properly, stop tightening the upper threaded spindle rods just before the outer housing of the arched handle latch and the receiving component touch.

STEP 8




NOTE: There should be equal spacing among each of the (4) threaded spindle rods. Make the appropriate adjustment to ensure you have installed your gate safely.

STEP 9




Position the gate so that it is level and centered within your doorway or opening. Rotate the adjustment wheels on the threaded spindle rods in the opposite direction as in Step 4, expanding the gap between the rubber foot and the adjustment wheel. Expand each of the (4) threaded spindle rods until they make contact with the doorway or opening. Do not fully tighten the threaded spindle rods yet.

STEP 10




With gate fully removed, you can now use the circles you marked during Step 1 as guides for screwing in your (4) wall cups. Center each of the wall cups within the guide circles and use the provided self-tapping screws (G) to fasten them in place via the hole through the center of each wall cup.

STEP 11




Reinstall your gate in the doorway or opening according to the instructions, using the newly installed wall cups as anchoring points for the (4) threaded spindle rods.

STEP 12




Remove the top and bottom threaded spindle rods. Assemble the gate and extension as illustrated. Reposition the gate and fit in accordance with the gate fitting.

STEP 13




NOTE: It is preferable to install any extensions on the hinge side of the gate.

STEP 14



Hardware Kit #11055 includes: Threaded Spindle Rods w/ Adjustment Wheel (4), Spring Loaded Upper Door Mounting Pin (1), 1" Wall Mount Screws (4), Frame Assembly Screw (2), Wall Cups (4), Hex Key (1).

STEP 15



90 DAYS LIMITED WARRANTY
If, during the first 90 days after consumer purchase of the item, under reasonable and non-commercial use and conditions of maintenance, it fails while owned by the original purchaser because of the quality of materials or workmanship of finish and assembly, Regalo International, LLC, will replace or repair it at Regalo's option. PROOF OF PURCHASE REQUIRED.




Arched Decor Safety Gate

Barrière Arquée Décorative de Sécurité

Puerta Decorativa Arqueada de Seguridad

Models / Modèles / Modelos: 0370BR, 0380BR



• READ ALL INSTRUCTIONS BEFORE ASSEMBLY AND USE OF GATE. KEEP INSTRUCTIONS FOR FUTURE USE.

• LIRE TOUTES LES INSTRUCTIONS AVANT D'ASSEMBLER ET D'UTILISER LA BARRIÈRE. CONSERVER CES INSTRUCTIONS POUR UNE UTILISATION ULTÉRIEURE.

• LEA TODAS LAS INSTRUCCIONES ANTES DE MONTAR Y USAR LA REJA. GUÁRDELAS PARA UTILIZARLAS COMO REFERENCIA.

www.regalo-baby.com


Regalo International, LLC.

3200 Corporate Center Drive, Suite 100 / Burnsville, MN 55306, USA / , É.-U. / , EE. UU.

866.272.5274 (U.S. only / aux États-Unis seulement / solo en EE. UU.) or / ou / o 952.435.1080

Made in China / Fabriqué en Chine / Hecha en China

Before Assembly



PLEASE CHECK TO MAKE SURE YOU HAVE THE FOLLOWING PARTS:

- | | |
|------------------------------------|--|
| A Left Side Frame Half (1) | F Wall Cups (4) |
| B Gate Door Panel (1) | G 1" Wall Mount Screws (4) |
| C Right Side Frame Half (1) | H Spring Loaded Upper Door Mounting Pin (1) |
| D 4" Extension (1) | I Frame Assembly Screws (2) |
| E Threaded Spindle Rods (4) | J Hex Key (1) |

NOTE

MODEL NO. MAX SIZE

0370	29 ↔ 35 in, ↑ 30 in tall
0380	29 ↔ 35 in, ↑ 36 in tall

BEFORE USING PRODUCT

Read and follow all instructions carefully to ensure that your gate and extensions are properly installed. Improper installation could result in the gate becoming unstable or dislodged from the doorway. Always make sure the extension is securely attached to the gate before using. The safety of your child is your responsibility. Please keep these instructions for your reference.

IMPORTANT

- Never use more than two extensions per side of gate.
- If hardware mounting to a surface other than drywall or wood, please consult with a professional about installation.
- Base locks are to be used at all times, on both sides of the gate.

REMOVING YOUR GATE FROM THE WALL


To remove your gate from the wall, rotate the adjustment wheels on each of the (4) threaded spindle rods to depressurize the gate from its doorway or opening. Then, gently pull or push the gate free from its doorway or opening.

CARE AND MAINTENANCE

Periodically check the gate for signs of damage, wear, or missing components. Do not use if any part is missing, worn or damaged. Check the gate regularly to ensure all the hardware and mountings are tightened. Do not use abrasive cleaners or bleach. Clean by sponging with warm water and a mild detergent.


Assembling and Installing Your Gate

STEP 1




Take the left (A) and right (C) gate frame halves and align the holes in the lower horizontal tube. Place the frame halves together and then using the frame assembly screws (I), tighten the two halves together.

STEP 2




Lower the gate door (B) into the assembled gate frame and insert the lower gate door pin into the mounting hole on the frame.

STEP 3




ÉTAPE 7



Une fois satisfait de la position globale de votre barrière, serrez fermement les tiges filetées fixées aux coins inférieurs de la barrière en continuant de tourner les molettes. Serrez ensuite fermement les tiges filetées supérieures. À mesure que vous serrez les tiges filetées supérieures, vous constaterez que l'espace se resserre entre le cadre de la porte et le loquet de la poignée arquée. Pour que la barrière fonctionne bien, arrêtez de serrer les molettes des tiges filetées supérieures juste avant que le cadre de la barrière ne touche le côté du loquet.

REMARQUE : Les quatre (4) tiges filetées devraient être espacées également. Effectuez le réglage approprié pour que la barrière installée soit sécuritaire.


ÉTAPE 1



Tirez la détente inférieure vers le haut tout en tirant le bouton coulissant supérieur vers l'arrière. La combinaison de ces deux actions libérera le verrou et permettra à la barrière de s'ouvrir librement. Poussez ou tirez pour ouvrir la porte de la barrière. Pour la fermer, il suffit de pousser ou de tirer dessus pour la remettre à sa position d'origine. Le loquet de la poignée arquée se réengagera automatiquement et verrouillera la porte en position fermée.

REMARQUE : Si le loquet de la poignée arquée ne s'engage pas correctement dans l'élément de réception, assurez-vous que votre barrière est de niveau, qu'elle est correctement montée et que vous n'avez pas trop serré les tiges filetées.


ÉTAPE 2



En bas du portillon, tournez le verrou de base à la position horizontale. Pour permettre au portillon d'ouvrir dans une seule direction, tournez le verrou de base sur un des côtés. Pour permettre au portillon d'ouvrir dans les deux directions, tournez le verrou de base sur les deux côtés.


REMARQUE : Mettre le verrou sur le côté occupé par l'enfant.

ÉTAPE 1




Après le montage de la barrière en position satisfaisante, tracez un cercle sur la surface de l'embrasure de la porte ou dans l'ouverture autour du périmètre des quatre (4) pieds caoutchoutés. Retirez ensuite la barrière de l'ouverture en desserrant les quatre (4) tiges filetées pour libérer la barrière.

ÉTAPE 2




Une fois la barrière retirée, vissez les quatre (4) couppelles murales (F) dans les cercles guides tracés à L'ÉTAPE 1. Centrez chaque couppelle murale dans les cercles guides, puis utilisez les vis (G). Taraudeuses fournies pour les serrer en place par leur trou central.

ÉTAPE 3




Remontez votre barrière dans l'embrasure de la porte ou dans l'ouverture en suivant les instructions; utilisez les couppelles murales nouvellement installées comme points d'ancrage des quatre (4) tiges filetées.

ÉTAPE 1




Enlevez les tiges filetées supérieure et inférieure. Joignez la rallonge à la barrière, tel qu'illustré. Remplacez la barrière et ajustez-la conformément aux instructions d'encastrement.

ÉTAPE 2




REMARQUE : Il est préférable de poser les rallonges sur le côté des charnières de la barrière.

ÉTAPE 1



Trousse de Quincaillerie #11055 Inclut :
Tiges filetées avec molette (4), Tige de montage de porte supérieure actionnée par ressort (1), Vis murales 2,5 cm (1 po) (4), Vis de cadre (2), Coupelles murales (4), Clé hexagonale (1)




ÉTAPE 2



GARANTIE LIMITÉE DE 90 JOURS
Si, au cours des 90 jours suivant l'achat de cet article, dans des circonstances raisonnables et dans des conditions d'utilisation et d'entretien non commerciales, l'article, qui appartient encore à l'acheteur original, s'avère défectueux en ce qui a trait à la qualité des matériaux ou aux travaux de finition et d'assemblage, Regalo International LLC le remplacera ou le réparera à son choix. PREUVE D'ACHAT REQUISE.

ÉTAPE 1



Vous avez besoin d'une largeur plus grande? Rallonges supplémentaires vendues séparément.
www.regalo-baby.com


ÉTAPE 2



0370 RALLONGES

- 4" Rallonges
Bronze n° = #1074 BR
- 6" Rallonges
Bronze n° = #1076 BR


ÉTAPE 3



0380 RALLONGES


- 4" Rallonges
Bronze n° = #1084 BR
- 6" Rallonges
Bronze n° = #1086 BR

ÉTAPE 1



Enlevez les tiges filetées supérieure et inférieure. Joignez la rallonge à la barrière, tel qu'illustré. Remplacez la barrière et ajustez-la conformément aux instructions d'encastrement.

ÉTAPE 2



REMARQUE : Il est préférable de poser les rallonges sur le côté des charnières de la barrière.

ÉTAPE 1



Trousse de Quincaillerie #11055 Inclut :
Tiges filetées avec molette (4), Tige de montage de porte supérieure actionnée par ressort (1), Vis murales 2,5 cm (1 po) (4), Vis de cadre (2), Coupelles murales (4), Clé hexagonale (1)




ÉTAPE 2




GARANTIE LIMITÉE DE 90 JOURS
Si, au cours des 90 jours suivant l'achat de cet article, dans des circonstances raisonnables et dans des conditions d'utilisation et d'entretien non commerciales, l'article, qui appartient encore à l'acheteur original, s'avère défectueux en ce qui a trait à la qualité des matériaux ou aux travaux de finition et d'assemblage, Regalo International LLC le remplacera ou le réparera à son choix. PREUVE D'ACHAT REQUISE.

ÉTAPE 1



Vous avez besoin d'une largeur plus grande? Rallonges supplémentaires vendues séparément.
www.regalo-baby.com


ÉTAPE 2



0370 RALLONGES

- 4" Rallonges
Bronze n° = #1074 BR
- 6" Rallonges
Bronze n° = #1076 BR


ÉTAPE 3



0380 RALLONGES


- 4" Rallonges
Bronze n° = #1084 BR
- 6" Rallonges
Bronze n° = #1086 BR

ÉTAPE 1



Enlevez les tiges filetées supérieure et inférieure. Joignez la rallonge à la barrière, tel qu'illustré. Remplacez la barrière et ajustez-la conformément aux instructions d'encastrement.

ÉTAPE 2



REMARQUE : Il est préférable de poser les rallonges sur le côté des charnières de la barrière.


ÉTAPE 1



Trousse de Quincaillerie #11055 Inclut :
Tiges filetées avec molette (4), Tige de montage de porte supérieure actionnée par ressort (1), Vis murales 2,5 cm (1 po) (4), Vis de cadre (2), Coupelles murales (4), Clé hexagonale (1)




ÉTAPE 2




GARANTIE LIMITÉE DE 90 JOURS
Si, au cours des 90 jours suivant l'achat de cet article, dans des circonstances raisonnables et dans des conditions d'utilisation et d'entretien non commerciales, l'article, qui appartient encore à l'acheteur original, s'avère défectueux en ce qui a trait à la qualité des matériaux ou aux travaux de finition et d'assemblage, Regalo International LLC le remplacera ou le réparera à son choix. PREUVE D'ACHAT REQUISE.

ÉTAPE 1



Vous avez besoin d'une largeur plus grande? Rallonges supplémentaires vendues séparément.
www.regalo-baby.com


ÉTAPE 2



0370 RALLONGES

- 4" Rallonges
Bronze n° = #1074 BR
- 6" Rallonges
Bronze n° = #1076 BR

ÉTAPE 3



0380 RALLONGES

- 4" Rallonges
Bronze n° = #1084 BR
- 6" Rallonges
Bronze n° = #1086 BR

ÉTAPE 1




Enlevez les tiges filetées supérieure et inférieure. Joignez la rallonge à la barrière, tel qu'illustré. Remplacez la barrière et ajustez-la conformément aux instructions d'encastrement.

ÉTAPE 2



REMARQUE : Il est préférable de poser les rallonges sur le côté des charnières de la barrière.

ÉTAPE 1



Trousse de Quincaillerie #11055 Inclut :
Tiges filetées avec molette (4), Tige de montage de porte supérieure actionnée par ressort (1), Vis murales 2,5 cm (1 po) (4), Vis de cadre (2), Coupelles murales (4), Clé hexagonale (1)




ÉTAPE 2




GARANTIE LIMITÉE DE 90 JOURS
Si, au cours des 90 jours suivant l'achat de cet article, dans des circonstances raisonnables et dans des conditions d'utilisation et d'entretien non commerciales, l'article, qui appartient encore à l'acheteur original, s'avère défectueux en ce qui a trait à la qualité des matériaux ou aux travaux de finition et d'assemblage, Regalo International LLC le remplacera ou le réparera à son choix. PREUVE D'ACHAT REQUISE.

ÉTAPE 1



Vous avez besoin d'une largeur plus grande? Rallonges supplémentaires vendues séparément.
www.regalo-baby.com

ÉTAPE 2



0370 RALLONGES

- 4" Rallonges
Bronze n° = #1074 BR
- 6" Rallonges
Bronze n° = #1076 BR


ÉTAPE 3



0380 RALLONGES


- 4" Rallonges
Bronze n° = #1084 BR
- 6" Rallonges
Bronze n° = #1086 BR

ÉTAPE 1




Enlevez les tiges filetées supérieure et inférieure. Joignez la rallonge à la barrière, tel qu'illustré. Remplacez la barrière et ajustez-la conformément aux instructions d'encastrement.

ÉTAPE 2




REMARQUE : Il est préférable de poser les rallonges sur le côté des charnières de la barrière.

ÉTAPE 1



Trousse de Quincaillerie #11055 Inclut :
Tiges filetées avec molette (4), Tige de montage de porte supérieure actionnée par ressort (1), Vis murales 2,5 cm (1 po) (4), Vis de cadre (2), Coupelles murales (4), Clé hexagonale (1)



ÉTAPE 2



GARANTIE LIMITÉE DE 90 JOURS
Si, au cours des 90 jours suivant l'achat de cet article, dans des circonstances raisonnables et dans des conditions d'utilisation et d'entretien non commerciales, l'article, qui appartient encore à l'acheteur original, s'avère défectueux en ce qui a trait à la qualité des matériaux ou aux travaux de finition et d'assemblage, Regalo International LLC le remplacera ou le réparera à son choix. PREUVE D'ACHAT REQUISE.

ÉTAPE 1



Vous avez besoin d'une largeur plus grande? Rallonges supplémentaires vendues séparément.
www.regalo-baby.com

ÉTAPE 2



0370 RALLONGES

- 4" Rallonges
Bronze n° = #1074 BR
- 6" Rallonges
Bronze n° = #1076 BR

ÉTAPE 3



0380 RALLONGES


- 4" Rallonges
Bronze n° = #1084 BR
- 6" Rallonges
Bronze n° = #1086 BR

ÉTAPE 1




Enlevez les tiges filetées supérieure et inférieure. Joignez la rallonge à la barrière, tel qu'illustré. Remplacez la barrière et ajustez-la conformément aux instructions d'encastrement.

ÉTAPE 2



REMARQUE : Il est préférable de poser les rallonges sur le côté des charnières de la barrière.


ÉTAPE 1



Trousse de Quincaillerie #11055 Inclut :
Tiges filetées avec molette (4), Tige de montage de porte supérieure actionnée par ressort (1), Vis murales 2,5 cm (1 po) (4), Vis de cadre (2), Coupelles murales (4), Clé hexagonale (1)




ÉTAPE 2




GARANTIE LIMITÉE DE 90 JOURS
Si, au cours des 90 jours suivant l'achat de cet article, dans des circonstances raisonnables et dans des conditions d'utilisation et d'entretien non commerciales, l'article, qui appartient encore à l'acheteur original, s'avère défectueux en ce qui a trait à la qualité des matériaux ou aux travaux de finition et d'assemblage, Regalo International LLC le remplacera ou le réparera à son choix. PREUVE D'ACHAT REQUISE.

ÉTAPE 1



Vous avez besoin d'une largeur plus grande? Rallonges supplémentaires vendues séparément.
www.regalo-baby.com


ÉTAPE 2



0370 RALLONGES

- 4" Rallonges
Bronze n° = #1074 BR
- 6" Rallonges
Bronze n° = #1076 BR

ÉTAPE 3



0380 RALLONGES

- 4" Rallonges
Bronze n° = #1084 BR
- 6" Rallonges
Bronze n° = #1086 BR