

DATA SHEET

Kit for recessed machflow®

KT0009CS

General Description

- Kit for recessed machflow® hand dryer (hand dryer not included).
- The kit for recessed machflow® makes the machflow® hand dryer suitable for the compliance of the ADAAG norm (US) – that limits to 4” the horizontal projection of the devices installed in bathrooms for public use –, bestowing on that hand dryer the quality of “specific for the disabled”.
- Maximum robustness and vandal-proofness.
- Excellent integration and aesthetical level.

Components & Materials

- KT0010CS: stainless steel AISI 304 kit for recessed Machflow hand dryer (hand dryer not included), satin finish.
- CABINET: made in two welded parts. The dryer mounting areas are fabricated of 20GA 18-8 type AISI304 stainless steel, it includes 4 M5 bolts welded on top of the base plate for fitting of the machflow® hand dryer.
- FRAME: made in 22GA 18-8 type AISI304 stainless steel with 4 screw holes of Ø 1/4” (6,5mm) for mounting on the wall.
- Nuts and bolts for the fitting of the hand dryer to the kit included: 4 nuts DIN 934 M5, 4 washers DIN 9021 M5 and 4 rubber silent blocks 8 x 18mm.

NOTE 1: Machflow hand dryer not included.

NOTE 2: The screws and wall plugs for the mounting of the cabinet to the wall are not included. The use of stainless steel screws is recommended.

Technical Specifications

Cabinet dimensions - 23 3/8” H x 14 3/4” W x 3” D	Rough Wall Opening – 21 5/8” H x 13” W x 3 3/8” D
Outer projection from the wall - 3 55/64”	Wall accommodation – 3 3/8” depth

Operation

No specific instructions for its use required.

Please mark the selected item



code

KT0009CS

material

stainless steel

finish

satin

Saniflow Corp reserves the right to make changes and/or modifications to the products and their specifications without warning or notice.

For further info please contact SANIFLOW on: Toll free: 1-877-222-9125 or visit our website at www.saniflowcorp.com

Tel: +1 (305) 424 2433 Fax: +1 (305) 424 2435 · sales@saniflowcorp.com

