THANK YOU
FOR YOUR PURCHASE!

DO NOT APPLY IN COLD WEATHER (BELOW 50 DEGREES) VINYL BECOMES BRITTLE
DO NOT APPLY IN EXTREME HEAT (ABOVE 90 DEGREES)
VINYL BECOMES SOFT AND STRETCHY
DO NOT USE RUBBING ALCOHOL TO APPLY - IT DESTROYS THE ADHESIVE
DO NOT TOUCH THE ADHESIVE BACKING OF THE DECAL
DO NOT BE ALARMED IF YOUR DECAL CAME IN TWO PARTS.
IN MANY CASES THE DECAL IS EASIER TO MANAGE WHEN IT NOT SO BIG

HOW TO APPLY

1. CLEAN:
WIPE THE SURFACE YOU ARE APPLYING THE DECAL
TO WITH A DAMP CLOTH (WATER ONLY). DRY BEFORE APPLYING .

2. MEASURE AND LEVEL:
DETERMINE THE DESIRED LOCATION AND MEASURE FOR
PLACEMENT USING A LEVEL. MAKE SURE THE DECAL IS
LEVEL AND POSITIONED SYMMETRICALLY.

3. SECURE WITH TAPE:
WHILE STILL HOLDING THE LEVELED POSITION, PLACE A FEW
PIECES OF TAPE AT THE TOP OF YOUR DECAL.

4. TAPE IN PLACE:
APPLY ANOTHER PIECE OF TAPE (HORIZONTALLY) ACROSS THE TOP
OF THE VINYL GRAPHIC.

5. REMOVE BACKING PAPER:
WITH THE TAPE FUNCTIONING AS A HINGE, FLIP THE VINYL
OVER AND CAREFULLY REMOVE THE BACKING PAPER FROM
THE GRAPHIC.

6. APPLY THE GRAPHIC
SLOWLY LOWER THE GRAPHIC IN PLACE APPLYING
PRESSURE USING A CREDIT CARD. WORKING FROM THE
CENTER OF THE GRAPHIC TO THE EDGE.

7. REMOVE TRANSFER TAPE
CAREFULLY AND SLOWLY PEEL AWAY THE TRANSFER TAPE AT
A 45 DEGREE DOWNWARD ANGLE.

DECAL REMOVAL

GO OVER THE DECAL AREA WITH A BLOW DRYER ON LOW HEAT
FOR APPROXIMATELY 30-60 SECONDS. THIS SOFTENS THE ADHESIVE BACKING
ON THE DECAL AND MAKES IT PLYABLE AND EASY TO REMOVE