



see what Delta can do™

SHOWER ARM WITH SHOWER HEAD

■ Bell Shower Head with Adjustable Arm Extender

FEATURES:

- Touch-Clean® Spray Holes

STANDARD SPECIFICATIONS:

- Max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa (75372 only)
- Max flow rate 2.5 gpm @ 80 psi, 9.5 L/min @ 550 kPa (75372D only)
- 3-spray setting shower head with adjustable arm - pause is a non-positive shut-off
- Ball connector swivel angle is 30° (15° per side)
- Change spray modes with easy turn dial
- Fits standard 1/2"-14 NPT pipe fitting
- 3 Spray settings include: Full Body spray, Massaging spray and Pause

WARRANTY:

- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense® -Applies to 75372 only

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-75372 Rev. B

Delta Faucet Company

55 E. 111th Street, Carmel, IN 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2025 Delta Faucet Company