




- Superior Grade 44mm Finish Interlocking Logs
- 95x95mm Heavy Duty Corner Posts
- Easy To Assemble Interlock System
- 2x Integral Heavy Duty Bench Seats
- Convenient In Built Wall Shelf

Cladding Material	Heavy Duty Interlocking T&G Logs	Cladding Thickness	44
Framing Style	Tanalised Bearers Only	Framing Size	58mm x 44mm
Roof Material	T&G Boarding	Roof Thickness	19mm
Floor Material	No Floor	Floor Size	0mm
Door Style	Opening Only	Door Size	0mm x 0mm
Window Style	n/a	Window Size	0mm x 0mm
Glazing Thickness	0	Glazing Material	n/a
Roof Covering	Black Mineral Felt	Treatment	Untreated
Locking System	None	Material	Selected European Softwoods

8x8:



Building Dimension	Length	Width	Base Size	Internal Size	External Ridge	External Eaves	Internal Ridge	Internal Eaves	Ext. Size exc. Roof	Ext. Size inc. Roof	No. of Windows	Weight
Outdoor Shelter 44mm Log Cabin	2350mm	2350mm	2160mm x 2160mm	2072mm x 2072mm	2623mm	2189mm	2411mm	2189mm	2350mm x 2350mm	2550mm x 2550mm	0	468kgs