

Free Standing Pet Gate Assembly Instructions

Parts List

	Pre-Assembled Gate Panels	2
11	Feet	2
	Feet Attachment Bolts (pre-inserted into bottom of gate)	2
	3/4" Rubber Support Bumpers	2
	Rubber Floor Protector Bumpers	4

Philips Head Screwdriver (Not Included) is needed for assembly.

Step 1

Turn the pre-assembled gate panels upside down and apply the ¾" Rubber Support Bumpers onto the center of each of the 2" plastic glides. Ensure that the surface is clean and dry when applying the bumpers for proper adhesion.

Step 2

Turn the feet upside down so that the counter sunk hole is facing up. Apply the Rubber Floor Protector Bumpers onto each end of the foot, about 1" from the edge.

Step 3

Remove the feet attachment bolts from the bottom of the gate and insert the Feet Attachment Bolts into the feet from the bottom side so that the bolt head recesses into the foot. Attach the feet to the frame by tightening the bolts using a Phillips Head Screwdriver until the bolts are snug and the foot is firmly attached. Turn your gate over onto its feet and it is now ready for use.

Please visit our website to view more of our pet products.

Usage Instructions

- •Your Freestanding Pet Gate is designed to be easily adjustable with no tools required.
- •For effortlessly opening, lift the gate slightly off of the floor, slide the panels apart to the desired width and set the gate back down.
- •For storage or transport, slide your gate into a closed position and rotate the feet in line with the gate.
- •This product is designed for use with small animals that can not jump over or push the gate out of position.

Cautions

- •Place this product on a flat, even surface.
- •Do not carry a baby or infant when stepping over the gate.
- •Keep this product away from fire or extremely high temperatures.
- •Do not use this product for anything other than its intended purpose.
- •This product is designed for indoor use only.
- •Do not lean or sit on this product.
- •Use a damp cloth to wipe clean.
- •Use of chemicals or harsh abrasives could damage the finish of this product.