

CODE NUMBER

3345100

DESCRIPTION

Polished Chrome Finish, Single Flush, Hardwired, Exposed Sensor Hardwired Urinal/Water Closet Retrofit Flushometer.

DETAILS

Finish: Polished Chrome (CP)Power Type: Hardwired (HW)

• Valve: Diaphragm

Valve Body Material: Semi-red Brass
Fixture Type: Urinal/Water Closet
Fixture Connection: Top spud

FEATURES

- Non-Hold-Open True Mechanical Override Full Flush Button
- User-friendly three (3) second flush delay
- "User in View" Flashing LED
- No External Volume Adjustment to Ensure Water Conservation The Side Mount units can be used on standard rough-in Sloan, Royal, Regal and Zurn flushometers.



COMPLIANCES & CERTIFICATIONS











(ADA Compliant, BREEAM Water Credit, cUPC Certified, Green Globes Water Credit, UL Certified)

RECOMMENDED SPECIFICATION

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi- Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

VALVE OPERATING PRESSURE (FLOWING)

15-80 PSI (103-552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- EL-700/750-A Installation Instructions
- Additional Downloads

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the EL700A product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer.
Find a compatible water closet for this flushometer.



ROUGH-IN

EL-700-A Single-Rush SideMount Hardwired unit EL-700-A Single-Flush SideMount Hardwired unit shown on an existing Royal 111 closet flushometer shown on an existing Royal 186 urinal flushometer 43/4" 43/4" 2-1/4" MIN. 2-1/4" MIN. (178 mm) (178 mm) (121 mm) (121 mm) (57 mm) 1" I.P.S. SUPPLY 1" I.P.S. SUPPLY (57 mm) 6" 6" 2-3/4" (70 mm) 2-3/4" (70 mm) (131 mm) (131 mm) (DN 25 mm) (DN 25 mm) 2" ((C/L OF SUPPLY C/L OF SUPPLY 11¹/2" (292 mm) 11¹/2" (292 mm) __ 7-1/2" _ (191 mm) — 7-1/2" — (191 mm) TOP OF FIXTURE TOP OF FIXTURE C/L OF FIXTURE C/L OF FIXTURE C/L OF FIXTURE C/L OF FIXTURE

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com