ACT3068 - Single Lever

Product Finish: Chrome **EAN13 barcode:** 5060879992443

Product features:

- Metal construction throughout
- Single lever control for effortless single handed control
- Solid and functional European architect design styling
- Antisplash spout supplied as standard
- Supplied complete with flexible tail pipes for fast simple fitting

Additional information / Parts included:

1 x triangular stabilizer, 2.5mm Allen key, self adhesive sink seal (sco06030)

Primary WRAS fittings number (see www.wras.co.uk):

2010360

Product dimensions:



- **Overall Height / projection:** 317 mm
- **Exit reach:** 219 mm
- **Exit height:** 298 mm
- **Centre distance(s):** n/a
- **Base diameter(s):** 50 mm
- **Recommended hole diameter:** Ø35 mm
- **Max. surface depth:** 70 mm
- **Spout diameter:** 30x10 mm
- **Spout aerator size:** M24

Packaged properties:

Box length: 435 mm
Box width: 340 mm
Tap only weight: 2.23 kg
Box depth: 70 mm
Units per outer: 5
Boxed weight: 2.84 kg

Product flow characteristics:



- **Min / Max water pressure:** 0.50 / 5.5 bar
- **Recommended / Max water temperature:** 46°C / 70°C
- **Part G - Mixed flow rate at 3 bar (litres / min):** 12.58

- **Control valve type:** 35mm Ø single lever ceramic cartridge
- **Flow characteristics:** Single flow
- **Non return valve(s):** Integral to Hot & Cold inlets

- **Aerator type:** Honeycomb aerator
- **Spout connection method:** Rear of body

- **Tail pipe inlet / outlet size:** M12 / 1/2" BSP Male
- **Inlet pipe type / length:** flexible stainless braided hose / 245 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

30/06/2023 - This sheet is a summary of the product information full details are available on request, errors & omissions excepted.