


# FIXTURE INSTALLATION INSTRUCTIONS

## ( Threaded pipe installation )

---



### CAUTION: DISCONNECT POWER DURING INSTALLATION

- 1.) If you are replacing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring from the outlet box.
- 2.) Screw the threaded pipe 3 complete turns into the mounting strap and lock in place with hex nut.
- 3.) Fasten the mounting plate to the outlet box using the two screws supplied with the outlet box.
- 4.) Spread the electrical wires so that the black wires are on one side of the outlet box and the white wires are on the other side.
- 5.) Grounding instructions:

A) On fixtures where mounting strap is provided with a green ground screw and two raised dimples. Wrap ground wire from outlet box around green ground screw and tighten.

B) On fixtures where mounting strap is provided with a green ground wire attached. Connect mounting strap ground wire to ground wire from outlet box with wire connector (not provided).

If fixture is provided with ground wire. Connect fixture ground wire to ground wire from outlet box with wire connector (not provided). After following the above steps.

Never connect ground wire to black or white power supply wires.

6.) To make electrical connections: Connect the white wire (s) from the fixture to the white wire of the outlet box. Connect the black wire(s) from the fixture to the black wire of the outlet box. NOTE: Black outlet box wire may be red, round & smooth and / or have copper conductor. White outlet box wire may be square & ridged and / or have a silver conductor.

7.) Place fixture against mounting surface allowing the machine screws to pass through the fixture cover plate. Secure with cap nuts.

