




ITEM #: RVY-WB5484-3

IMPORTANT SAFETY INSTRUCTIONS

- To avoid injury or damage, mount only on a surface that is sturdy.
- To avoid electric shock, make sure the electricity is turned off at the main circuit breaker panel. If you are replacing an existing fixture, turn off the following in order: fixture, wall switch, and main fuse or breaker box.
Note: Some types of fuses must be unscrewed to shut the power off.
- If you are unclear as to how to proceed, please consult a licensed electrician.


UNPACK THE FIXTURE: Check the contents of the box. Box should contain all items on the parts diagram.



For any replacement parts or installation issues, please Contact Us!
Email: help@kira-home.com
Facebook/Instagram: @KiraHomeDecor
Phone: 888.208.2085

INSTALLATION INSTRUCTIONS

1. Secure Mounting Plate (A) to existing junction box using Mounting Screws (B) provided. Use a leveling tool to ensure that Mounting Plate (A) is level.
Note: Mounting Plate (A) should be attached to the back of the fixture. Remove it.
2. Using the pre-drilled holes on Mounting Plate (A), mark location to install Plastic Anchors (H). Remove Mounting Plate (A) and drill pilot holes on the marked spots and insert Plastic Anchors (H).
Note: Plastic Anchors (H) should sit flush with the wall.
3. Re-secure Mounting Plate (A) to the junction box (not included) using Mounting Screws (B) and Anchor Screws (G) provided. Ensure Mounting Plate (A) is positioned with the brackets on the top and bottom.
4. Using the wire graph below, connect the appropriate wires from the fixture to the corresponding wires in the electrical junction box (not included) and secure Wire Connectors (C).



- A.** Connect the ground wire (bare copper or green) from your fixture to the:
 - 1) ground wire in the junction box, or
 - 2) ground screw in the junction box
- B.** Connect the BLACK house wire to fixture hot wire that corresponds to diagram (black, round & smooth, white/grey with tracer, brown/gold without tracer).
- C.** Connect the WHITE house wire to fixture neutral wire that corresponds to diagram (white, ribbed/ridged, white/grey without tracer, brown/gold with tracer).

5. Place all wires and Wire Connectors (C) back into the junction box.
6. Place Backplate Assembly (D) against the wall, ensuring holes on each side of Backplate Assembly (D) align with the holes on Mounting Plate (A). Secure Backplate Assembly (D) to Mounting Plate (A) with Backplate Screws (E).
7. Secure Shades (F) to Sockets (J) with Socket Rings (I).
Note: Socket Rings (I) should already be attached to Sockets (J). Remove Socket Rings (I) prior to installing Shades (F).
8. Install light bulbs (not included) into Sockets (J).

Enjoy your new fixture!

Kira Home

ITEM #: RVY-WB5484-3 - PARTS DIAGRAM

HELPFUL TOOLS: Safety Goggles, Screwdriver, Ladder, Measuring Tape

