

# R4RD2T, R4SD2T

4.5" Volta - Regressed

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## PRODUCT DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for the architectural lighting industry. This high lumen family of fixtures, with an extensive set of round and square fittings enables lighting designers an advanced system for a clean, uncluttered ceiling

## FEATURES

- Dual finishes are single piece, no physical seams
- Optimized cutoff for superior glare control
- Compatible with wide range of accessories

## SPECIFICATIONS

**Construction:** Durable die-cast self flanged aluminum construction

**Input:** 120 - 277VAC


**Dimming:** Electronic Low Voltage (ELV): 100%-5%  
0-10V: 100%-0%

**Mounting:** Two heavy gauge retention clips hold trim firmly  
Accommodates 1/2" - 1 1/2" ceiling thickness

**Finish:** Powder coated white, black and haze

**Standards:** ETL & cETL Wet location Listed

## TRIMS (ORDER HOUSING SEPARATELY)

Model	Beam Angle	Reference Output*		Color Temp	CRI	Finishes	Reflector/Trim
		Lumens	CBCP				
 <b>R4RD2T</b> <i>Round</i>	<b>S</b> 15°	1391	12282	<b>827</b> 2700K	85	<b>BK</b> Black	
	<b>N</b> 25°	2694	7980	<b>927</b> 2700K	90	<b>BKWT</b> Black/White	
	<b>F</b> 45°	2609	4347	<b>830</b> 3000K	85	<b>HZ</b> Haze	
	<b>W</b> 60°	2413	2679	<b>930</b> 3000K	90	<b>HZWT</b> Haze/White	
					<b>835</b> 3500K	85	<b>WT</b> White
<b>R4SD2T</b> <i>Square</i>	<b>S</b> 15°	1398	12724	<b>827</b> 2700K	85	<b>BK</b> Black	
	<b>N</b> 25°	2852	7634	<b>927</b> 2700K	90	<b>BKWT</b> Black/White	
	<b>F</b> 45°	2785	4295	<b>830</b> 3000K	85	<b>HZ</b> Haze	
	<b>W</b> 60°	2430	2422	<b>930</b> 3000K	90	<b>HZWT</b> Haze/White	
					<b>835</b> 3500K	85	<b>WT</b> White
				<b>840</b> 4000K	85		

\*Reference output shows **830**(80CRI 3000K) trim with **36** housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM					
	827	927	830	930	835	840
<b>HOUSING</b> 36	0.937	0.764	1.000	0.815	1.045	1.054
25	0.685	0.558	0.731	0.596	0.764	0.770
15	0.456	0.371	0.486	0.396	0.508	0.512

R4\_D2T-\_\_\_\_\_ - \_\_\_\_\_

Example: **R4RD2T-S827-HZWT**

Please see next page for housing units(required)

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# R4RD2T, R4SD2T

## 4.5" Volta - Regressed

# WAC LIGHTING

Responsible Lighting®

### HOUSINGS (REQUIRED)

		Model	Power*	S	N, F, W	Rating	Options
<b>New Construction, Airtight</b> 	<b>R4RNT</b> Round	<b>15</b> <b>25</b> <b>36</b>	10W 15W 23W	15W 25W 36W	IC rated IC rated Non-IC	<b>EM</b>	Emergency backup battery (Optional)
	<b>R4RCT</b> Round Chicago Plenum						
<b>New Construction, Airtight</b> 	<b>R4SNT</b> Square	<b>15</b> <b>25</b> <b>36</b>	10W 15W 23W	15W 25W 36W	IC rated IC rated Non-IC	<b>EM</b>	Emergency backup battery (Optional)
	<b>R4SCT</b> Square Chicago Plenum						
<b>Remodel</b> 	<b>R4BRT</b> Round or Square	<b>15</b> <b>25</b> <b>36</b>	10W 15W 23W	15W 25W 36W	Non-IC Non-IC Non-IC		N/A

\*Power consumption depends on beam angle of the trim.

## R4 -

Example: **R4RNT-15** or **R4RNT-15EM** (with Emergency backup battery)

### FIELD CHANGEABLE GLARE CONTROL AND OPTIC SYSTEM

Accessory holder  
Holds up to two lenses or  
One lens and one glare control



Optical cartridge  
Allows tool-less exchange of reflectors



Reflector  
For narrow flood, flood, and wide flood.  
Spot distribution features dedicated module.

#### Accessory holder

##### LENS-73-HLD

Required to hold lens and glare control accessories

#### Glare control accessories

##### LENS-73-HCL

Honeycomb Louver

##### LENS-73-CRL

Cross Louver

##### LENS-73-SNOOT

Snoot

#### Lens

##### LENS-73-AMB

Amber lens

##### LENS-73-RED

Red lens

##### LENS-73-FR

Frosted lens

##### LENS-73-SPR

Spread lens

##### LENS-73-BEL

Beam Elongating

#### Reflector

##### REF-R4-N

Narrow beam reflector

##### REF-R4-F

Flood beam reflector

##### REF-R4-W

Wide beam reflector

waclighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760