


IMPORTANT SAFETY INSTRUCTIONS

- To avoid injury or damage, mount only on a surface that is sturdy.
- To avoid electric shock, make sure the electricity is turned off at the main circuit breaker panel. If you are replacing an existing fixture, turn off the following in order: fixture, wall switch, and main fuse or breaker box.
Note: Some types of fuses must be unscrewed to shut the power off.
- If you are unclear as to how to proceed, please consult a licensed electrician.

UNPACK THE FIXTURE: Check the contents of the box. Box should contain all items on the parts diagram.

INSTALLATION INSTRUCTIONS

1. Secure Mounting Plate (A) to the junction box (not included) using Mounting Screws (B) provided. Ensure Mounting Plate (A) is positioned with Nipple (E) pointing away from the junction box.
2. Adjust Cord (G) and Weight (I) to desired hanging length by loosening the Wire Grip Screw (H) with provided Hex Wrench (O). Retighten Wire Grip Screw (H) when desired height has been achieved.
3. Place Canopy (D) flush against the ceiling by inserting Nipple (E) through the appropriate hole located on Canopy (D). Verify that 1/4" of the threaded portion of Nipple (E) is visible. Remove Canopy (D) and set it aside.
Note: If 1/4" of Nipple (E) is not visible, remove Canopy (D) and re-adjust Nipple (E) to proper height and lock it in place with the hex nuts.
4. Remove any excess Cord (G), leaving approximately 10 inches beyond desired hanging length.
5. Using the wire graph on the next page, connect the appropriate wires from the fixture to the corresponding wires in the electrical junction box (not included) and secure Wire Connectors (C).



- A.** Connect the ground wire (bare copper or green) from your fixture to the:
- 1) ground wire in the junction box, or
 - 2) ground screw in the junction box
- B.** Connect the BLACK house wire to fixture hot wire that corresponds to diagram (black, round & smooth, white/grey with tracer, brown/gold without tracer).
- C.** Connect the WHITE house wire to fixture neutral wire that corresponds to diagram (white, ribbed/ridged, white/grey without tracer, brown/gold with tracer).

6. Place all wires and Wire Connectors (C) back into the junction box.
7. Place Canopy (D) against the ceiling, ensuring Nipple (E) is protruding through the hole in Canopy (D). Secure Canopy (D) and the fixture in place with Decorative Cap (F).
8. Secure Handle (L) to Shade (J) with Handle Screw (K), Washer (M) and Handle Cap Nut (N).
9. Install light bulb (not included) into the socket.

Enjoy your new fixture!

HELPFUL TOOLS: Safety Goggles, Screwdriver, Ladder, Measuring Tape

